

INDUSTRIAL COMPONENT DATA

DILMF8-10(RAC24) 104410 Y7-104410 EATON ELECTRIC Contactor, 4p, 125A/AC1

Brand: EATON - MOELLER | Manufacturer Part Number: DILMF8-10(RAC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMF8-10(RAC24)
Catalog number	Y7-104410
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-E65BC4E957
Generated	2026-08-05

Product Overview

Contactor, 4p, 125A/AC1

DILMF8-10(RAC24)

Eaton Moeller® series DILMF Contactors for Semiconductor Industries acc. to SEMI F47, 380 V 400 V: 7 A, 1 N/O, RAC 24: 24 V 50/60 Hz, Screw terminals

Contactor, Application: Contactors for Semiconductor Industries acc. to SEMI F47, Contactors up to 150 A with electronic actuation, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Rated operational current AC-3 380 V 400 V: $I_e = 7\text{ A}$, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: $I_{th} = I_e = 22\text{ A}$, enclosed: $I_{th} = 18\text{ A}$, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: $I_{th} = 50\text{ A}$, enclosed: $I_{th} = 45\text{ A}$, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: $P = 2.2\text{ kW}$, 380 V 400 V: $P = 3\text{ kW}$, 660 V 690 V: $P = 3.5\text{ kW}$, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: $P = 1\text{ kW}$, 380 V 400 V: $P = 2.2\text{ kW}$, 660 V 690 V: $P = 2.9\text{ kW}$, Contacts N/O = Normally open: 1 N/O, Instructions: Contacts to EN 50 012., built-in suppressor circuit'

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMF contactor for semiconductor industries Catalog Number 104410 Model Code

DILMF8-10(RAC24) EAN 4015081042272 Product Length/Depth 97 mm Product Height 85 mm Product Width 45 mm

Product Weight 0.531 kg Certifications CSA

CSA Class No.: 2411-03, 3211-04

CSA-C22.2 No. 60947-4-1-14

UL

UL Category Control No.: NLDX

UL File No.: E29096

UL 60947-4-1

CE

CSA File No.: 012528

IEC/EN 60947-4-1 Catalog Notes Also tested according to AC-3e. Features & Functions

Fitted with: Built-in suppressor circuit Number Of Poles Three-pole General

Application Contactors for Semiconductor Industries acc. to SEMI F47 Product category Contactors Resistance per pole

2.65 mΩ Suitable for Also motors with efficiency class IE3

SEMI F47, Magnet systems Utilization category AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-1: Non-inductive or slightly inductive loads, resistance furnaces Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Electro Magnetic Compatibility

Emitted interference According to EN 60947-1 Interference immunity According to EN 60947-1 Electrical Rating

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 20 A Rated operational current (Ie) at AC-3, 220 V, 230 V, 240

V 7 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V 7 A Rated....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMF8-10(RAC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.