

INDUSTRIAL COMPONENT DATA

DILMF8-10(RAC240) 104413 Y7-104413 EATON ELECTRIC Timer module, 200-240VAC, 0.1-100s, on-delayed

Brand: EATON - MOELLER | Manufacturer Part Number: DILMF8-10(RAC240)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMF8-10(RAC240)
Catalog number	Y7-104413
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-C68B957812
Generated	2026-08-04

Product Overview

Timer module, 200-240VAC, 0.1-100s, on-delayed

DILMF8-10(RAC240)

Eaton Moeller® series DILMF Contactors for Semiconductor Industries acc. to SEMI F47, 380 V 400 V: 7 A, 1 N/O, RAC 240: 190 - 240 V 50/60 Hz, Screw terminals

Contactor, Application: Contactors for Semiconductor Industries acc. to SEMI F47, Contactors up to 150 A with electronic actuation, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Description: Contactors suitable for semi-conductor industry according to SEMI F47., Contactors hum-free , suitable for building services automation., Operating mechanism adjustable from 50 Hz to 400 Hz., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: Ie= 7 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: Ith =Ie= 22 A, enclosed: Ith= 18 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: Ith= 50 A, enclosed: Ith= 45 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 2.2 kW, 380 V 400 V: P= 3 kW, 660 V...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMF contactor for semiconductor industries Catalog Number 104413 Model Code

DILMF8-10(RAC240) EAN 4015081042302 Product Length/Depth 97 mm Product Height 85 mm Product Width 45 mm

Product Weight 0.531 kg Certifications CSA

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

CSA Class No.: 2411-03, 3211-04

CE

CSA File No.: 012528

UL

UL Category Control No.: NLDX

UL File No.: E29096

IEC/EN 60947-4-1 Catalog Notes Also tested according to AC-3e. Product specifications

Electrical connection type for auxiliary- and control-current circuit Screw connection Number Of Poles Three-pole 10.10

Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMF8-10(RAC240) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.