

INDUSTRIAL COMPONENT DATA

DILMP20(220VDC) 276989 Y7-276989 EATON ELECTRIC Industrial Automation Bussines and Industrial Control Device..

Brand: EATON - MOELLER | Manufacturer Part Number: DILMP20(220VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMP20(220VDC)
Catalog number	Y7-276989
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-3C794DD1A8
Generated	2026-08-02

Product Overview

Industrial Automation Bussines and Industrial Control Devices IEC Starters and Contactors

DILMP20(220VDC)

Eaton Moeller® series DILMP Contactor, 4 pole, 22 A, 220 V DC, DC operation

Contactor, Application: Contactors for 4 pole electric consumers, Contactors up to 200 A, 4 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, Connection technique: Screw terminals, Number of poles: 4 pole, 380 V 400 V: Ie= 12 A, Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: Ith=Ie= 22 A, enclosed: Ith= 18 A, Conventional free air thermal current, 1 pole open: Ith= 60 A, enclosed: Ith= 54 A, 220 V 230 V: P= 3.5 kW, 380 V 400 V: P= 5.5 kW, 660 V 690 V: P= 6.5 kW , Instructions: Contacts to EN 50 012., Voltage AC/DC: DC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMP 4-pole contactor Catalog Number 276989 Model Code DILMP20(220VDC)

EAN 4015082769895 Product Length/Depth 75 mm Product Height 68 mm Product Width 45 mm Product Weight 0.294 kg

Certifications VDE 0660

CSA Class No.: 2411-03, 3211-04

CSA

IEC/EN 60947

UL File No.: E29096

IEC/EN 60947-4-1

CE

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

UL

UL 60947-4-1

UL Category Control No.: NLDX Catalog Notes Contacts according to EN 50012 Features & Functions

Number Of Poles Four-pole General

Application Contactors for 4 pole electric consumers Lifespan, mechanical 10,000,000 Operations (AC operated)

10,000,000 Operations (DC operated) Operating frequency 5000 mechanical Operations/h (DC operated)

5000 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category Contactors

Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated

impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA (with actuation of A1 - A2 by the electronics with "0"

signal) Resistance per pole 3.5 mΩ Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running Voltage type DC Ambient conditions, mechanical

Shock resistance 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Mec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMP20(220VDC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.