

## INDUSTRIAL COMPONENT DATA

# DILMP45-11(24V50/60HZ)-PI 199306 EATON ELECTRIC 4-pole contactor,45A/AC-1,action. AC. Push-in

Brand: EATON - MOELLER | Manufacturer Part Number: DILMP45-11(24V50/60HZ)-PI



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | DILMP45-11(24V50/60HZ)-PI     |
| Catalog number  | Y7-199306                     |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-425759CE58                 |
| Generated       | 2026-08-05                    |

## Product Overview

4-pole contactor,45A/AC-1,action. AC. Push-in

Contactor, Application: Contactors for 4 pole electric consumers, Contactors up to 200 A, 4 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, Connection technique: Push in terminals, Number of poles: 4 pole, 380 V 400 V: I<sub>e</sub>= 25 A, Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I<sub>th</sub> =I<sub>e</sub>= 45 A, enclosed: I<sub>th</sub>= 36 A, Conventional free air thermal current, 1 pole open: I<sub>th</sub>= 117 A, enclosed: I<sub>th</sub>= 105 A, 220 V 230 V: P= 7.5 kW, 380 V 400 V: P= 11 kW, 660 V 690 V: P= 14 kW , Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Instructions: Contacts to EN 50 012., with mirror contact., Voltage AC/DC: AC operation

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                         |
|--------------|-----------------------------------------|
| Catalog path | EATON - MOELLER > Contactors up to 170A |
|--------------|-----------------------------------------|

## Additional Product Information

## General specifications

Product Name Eaton Moeller® series DILMP 4-pole contactor Catalog Number 199306 Model Code

DILMP45-11(24V50/60HZ)-PI EAN 4015081973903 Product Length/Depth 115 mm Product Height 85 mm Product Width 61 mm Product Weight 0.542 kg Certifications VDE 0660

IEC/EN 60947 Catalog Notes Also tested according to AC-3e. Features & Functions

Fitted with: Mirror contact Number Of Poles Four-pole General

Application Contactors for 4 pole electric consumers Lifespan, mechanical 10,000,000 Operations (AC operated) Operating frequency 5000 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category

Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA (with actuation of A1 - A2 by the electronics with "0" signal) Resistance per pole 2.7 m $\Omega$  Utilization category AC-3: Normal AC induction motors: starting, switch off during running

AC-1: Non-inductive or slightly inductive loads, resistance furnaces Ambient conditions, mechanical

Shock resistance 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms Climatic environmental conditions

Ambient operating temperat...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMP45-11(24V50/60HZ)-PI with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.