

INDUSTRIAL COMPONENT DATA

DILMP63(*V50HZ) 109845 EATON ELECTRIC Contactor, 4p, 63A/AC1

Brand: EATON - MOELLER | Manufacturer Part Number: DILMP63(*V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMP63(*V50HZ)
Catalog number	-
Category	Power contactor, AC switching
Minimum order	10 Pcs
Document ID	EO-56FD9E185A
Generated	2026-08-03

Product Overview

Contactor, 4p, 63A/AC1

Power Contactor; Connection screw; 4-pole; 63; AC-1; * V-50 Hz

Contactor, 4 pole, 63 A, *V 50 Hz, AC operation

Contactor, Application: Contactors for 4 pole electric consumers, Contactors up to 200 A, 4 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, Connection technique: Screw terminals, Number of poles: 4 pole, 380 V 400 V: I_e= 40 A, Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th}=I_e= 63 A, enclosed: I_{th}= 50 A, Conventional free air thermal current, 1 pole open: I_{th}= 162 A, enclosed: I_{th}= 146 A, 220 V 230 V: P= 12.5 kW, 380 V 400 V: P= 18.5 kW, 660 V 690 V: P= 23 kW , Instructions: Contacts to EN 50 012., Voltage AC/DC: AC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

Contactor, 4 pole, 63 A, *V 50 Hz, AC operation
Contactor, Application: Contactors for 4 pole electric consumers, Contactors up to 200 A, 4 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, Connection technique: Screw terminals, Number of poles: 4 pole, 380 V 400 V: I_e= 40 A, Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th}=I_e= 63 A, enclosed: I_{th}= 50 A, Conventional free air thermal current, 1 pole open: I_{th}= 162 A, enclosed: I_{th}= 146 A, 220 V 230 V: P= 12.5 kW, 380 V 400 V: P= 18.5 kW, 660 V 690 V: P= 23 kW, Instructions: Contacts to EN 50 012., Voltage AC/DC: AC operation
Delivery program

Product rangeContactorsApplicationContactors for 4 pole electric consumersSubrangeContactors up to 200 A, 4 poleUtilization categoryAC-1: Non-inductive or slightly inductive loads, resistance furnaces
NAC-3: Normal AC induction motors: starting, switch off during runningConnection techniqueScrew terminalsNumber of poles4 poleRated operational currentAC-1Conventional free air thermal current, 3 pole, 50 - 60 Hzat 40 °C [I_{th}=I_e]63 AAC-1Conventional free air thermal current, 3 pole, 50 - 60 Hzat 50 °C [I_{th}=I_e]60 AAC-1Conventional free air thermal current, 3 pole, 50 - 60 Hzat 55 °C [I_{th}=I_e]58 AAC-1Conventional free air thermal current, 3 pole, 50 - 60 Hzat 60 °C [I_{th}=I_e]54 AContact sequenceFor use withDILM150-XHI(A)(V)...

or

DILM1000-XHI11-SA

or

DI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMP63(*V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.