

INDUSTRIAL COMPONENT DATA

DILMS115-22(RDC24) 191718 Y7-191718 EATON ELECTRIC

Safety device, 3 pole+2N/O+2N/C, 55 kW/400V/AC3, DC opera..

Brand: EATON - MOELLER | Manufacturer Part Number: DILMS115-22(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMS115-22(RDC24)
Catalog number	Y7-191718
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-0D7380846F
Generated	2026-08-06

Product Overview

Safety device, 3 pole+2N/O+2N/C, 55 kW/400V/AC3, DC operated

DILMS115-22(RDC24)

Eaton Moeller® series DILMS Safety contactor, 380 V 400 V: 55 kW, 2 N/O, 2 NC, RDC 24: 24 - 27 V DC, DC operation, Screw terminals, integrated suppressor circuit in actuating electronics

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMS Safety contactor Catalog Number 191718 Model Code DILMS115-22(RDC24)

EAN 4015081922314 Product Length/Depth 175 mm Product Height 170 mm Product Width 90 mm Product Weight 2.31 kg

Certifications CSA Class No.: 2411-03, 3211-04

CSA File No.: 012528

IEC/EN 60947

VDE 0660

UL 60947-4-1

UL File No.: E29096

CE

UL

CSA

UL Category Control No.: NLDX

IEC/EN 60947-4-1

CSA-C22.2 No. 60947-4-1-14 Catalog Notes Contacts according to EN 50012 General

Application Contactors for Motors Degree of protection IP00 Emitted interference According to EN 60947-1 Fitted with:
Mirror contact

Suppressor circuit in actuating electronics Interference immunity According to EN 60947-1 Lifespan, mechanical 10,000,000

Operations (DC operated) Operating frequency 3600 mechanical Operations/h (DC operated) Overvoltage category III

Pollution degree 3 Product category Safety contactors Protection Finger and back-of-hand proof, Protection against direct

contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA

(with actuation of A1 - A2 by the electronics with "0" signal) Resistance per pole 0.6 m Ω Shock resistance 10 g, N/O main

contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMS115-22(RDC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.