

INDUSTRIAL COMPONENT DATA

DILMS150-22(RAC120) 191731 Y7-191731 EATON ELECTRIC

Safety device, 3 pole + 2 N/O + 2 N/C, 75 kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILMS150-22(RAC120)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMS150-22(RAC120)
Catalog number	Y7-191731
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-995260A9CE
Generated	2026-08-05

Product Overview

Safety device, 3 pole + 2 N/O + 2 N/C, 75 kW/400V/AC3

DILMS150-22(RAC120)

Safety contactor, 380 V 400 V: 75 kW, 2 N/O, 2 NC, 110 V 50 Hz, 120 V 60 Hz, AC operation, Screw terminals, integrated suppressor circuit in actuating electronics

Safety contactor, Application: Contactors for Motors, Complete devices up to 170 A, Utilization category: AC-1:

Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Description: Auxiliary contact element connected non-detachably with basic device (manual activation not possible). , Rated operational current AC-3 380 V 400 V: Ie= 150 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: Ith =Ie= 190 A, enclosed: Ith= 144 A, Rated operational current AC-1

Conventional free air thermal current, 1 pole open: Ith= 400 A, enclosed: Ith= 360 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 48 kW, 380 V 400 V: P= 75 kW, 660 V 690 V: P= 96 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 20 kW, 380 V 400 V: P= 33 kW, 660 V 690 V: P= 48 kW, C...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

Safety contactor, 380 V 400 V: 75 kW, 2 N/O, 2 NC, 110 V 50 Hz, 120 V 60 Hz, AC operation, Screw terminals, integrated suppressor circuit in actuating electronicsSafety contactor, Application: Contactors for Motors, Complete devices up to 170

A, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Description: Auxiliary contact element connected non-detachably with basic device (manual activation not possible)., Rated operational current AC-3 380 V 400 V: $I_e = 150$ A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: $I_{th} = I_e = 190$ A, enclosed: $I_{th} = 144$ A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: $I_{th} = 400$ A, enclosed: $I_{th} = 360$ A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: $P = 48$ kW, 380 V 400 V: $P = 75$ kW, 660 V 690 V: $P = 96$ kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: $P = 20$ kW, 380 V 400 V: $P = 33$ kW, 660 V 690 V: $P = 48$ kW, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Instructions: Contacts to EN 50 012., integrated suppressor circuit in actuating electronics, with mir...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMS150-22(RAC120) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.