

INDUSTRIAL COMPONENT DATA

DILMS17-23(RDC24) 191710 Y7-191710 EATON ELECTRIC

Safety device, 3 pole+2N/O+3N/C, 7,5 kW/400V/AC3, DC opera..

Brand: EATON - MOELLER | Manufacturer Part Number: DILMS17-23(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMS17-23(RDC24)
Catalog number	Y7-191710
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-727B921F75
Generated	2026-08-05

Product Overview

Safety device, 3 pole+2N/O+3N/C, 7,5 kW/400V/AC3, DC operated

DILMS17-23(RDC24)

Eaton Moeller® series DILMS Safety contactor, 380 V 400 V: 7.5 kW, 2 N/O, 3 NC, RDC 24: 24 - 27 V DC, DC operation, Screw terminals, with mirror contact.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMS Safety contactor Catalog Number 191710 Model Code DILMS17-23(RDC24)

EAN 4015081922239 Product Length/Depth 138 mm Product Height 85 mm Product Width 45 mm Product Weight 0.613 kg

Certifications CSA File No.: 012528

VDE 0660

IEC/EN 60947-4-1

CSA-C22.2 No. 60947-4-1-14

CE

UL File No.: E29096

UL Category Control No.: NLDX

CSA Class No.: 2411-03, 3211-04

UL

CSA

IEC/EN 60947

UL 60947-4-1 Catalog Notes Contacts according to EN 50012 General

Application Contactors for Motors Degree of protection IP00 Emitted interference According to EN 60947-1 Fitted with:
Suppressor circuit in actuating electronics

Mirror contact Interference immunity According to EN 60947-1 Lifespan, mechanical 10,000,000 Operations (DC operated)

Operating frequency 5000 mechanical Operations/h (DC operated) Overvoltage category III Pollution degree 3 Product

category Safety contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from

front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 2.7 m Ω Shock resistance 3.5 g,

N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5.3 g, N/O auxiliary contact, Mechanical, accordi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMS17-23(RDC24) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.