


INDUSTRIAL COMPONENT DATA

**DILMS25-R23(110V50HZ,120V60HZ) 191737 Y7-191737 EATON
ELECTRIC Safety device, 3 pole + 2 N/O + 3 N/C, electr..**

Brand: EATON - MOELLER | Manufacturer Part Number: DILMS25-R23(110V50HZ,120V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMS25-R23(110V50HZ,120V60HZ)
Catalog number	Y7-191737
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-8E613BA8A5
Generated	2026-08-06

Product Overview

Safety device, 3 pole + 2 N/O + 3 N/C, electronically-compatible auxiliary contact, 11 kW/400V/AC3

DILMS25-R23(110V50HZ,120V60HZ)

Eaton Moeller® series DILMS Safety contactor, 380 V 400 V: 11 kW, 2 N/O, 3 NC, 110 V 50 Hz, 120 V 60 Hz, AC operation, Screw terminals, With mirror contact (not for microswitches).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMS Safety contactor Catalog Number 191737 Model Code

DILMS25-R23(110V50HZ,120V60HZ) EAN 4015081922505 Product Length/Depth 138 mm Product Height 85 mm Product

Width 45 mm Product Weight 0.476 kg Certifications IEC/EN 60947-4-1

UL 60947-4-1

CSA Class No.: 2411-03, 3211-04

CE

CSA File No.: 012528

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096

UL

VDE 0660

CSA

UL Category Control No.: NLDX Catalog Notes Contacts according to EN 50012 General

Application Contactors for Motors Degree of protection IP00 Emitted interference According to EN 60947-1 Fitted with:

Electronically compatible microswitch N/C

Electronically compatible microswitch N/O

Mirror contact (not for microswitches) Interference immunity According to EN 60947-1 Lifespan, mechanical 10,000,000

Operations (AC operated) Operating frequency 5000 mechanical Operations/h (AC operated) Overvoltage category III

Pollution degree 3 Product category Safety contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 2.7

m Ω ? Shock resistance 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

3.5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMS25-R23(110V50HZ,120V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.