

INDUSTRIAL COMPONENT DATA

DILMS32-R23(RDC24) 191726 Y7-191726 EATON ELECTRIC

Safety device, 3 pole+2N/O+3N/C, electronically-compatible.

Brand: EATON - MOELLER | Manufacturer Part Number: DILMS32-R23(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMS32-R23(RDC24)
Catalog number	Y7-191726
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-494880DA3C
Generated	2026-08-04

Product Overview

Safety device, 3 pole+2N/O+3N/C, electronically-compatible auxiliary contact, 15 kW/400V/AC3, DC operated DILMS32-R23(RDC24)

Eaton Moeller® series DILMS Safety contactor, 380 V 400 V: 15 kW, 2 N/O, 3 NC, RDC 24: 24 - 27 V DC, DC operation, Screw terminals, With mirror contact (not for microswitches).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMS Safety contactor Catalog Number 191726 Model Code DILMS32-R23(RDC24)
EAN 4015081922390 Product Length/Depth 138 mm Product Height 85 mm Product Width 45 mm Product Weight 0.613 kg
Certifications CE

UL

VDE 0660

CSA File No.: 012528

CSA

CSA Class No.: 2411-03, 3211-04

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-4-1

UL 60947-4-1

IEC/EN 60947

UL Category Control No.: NLDX

UL File No.: E29096 Catalog Notes Contacts according to EN 50012 General

Application Contactors for Motors Degree of protection IP00 Emitted interference According to EN 60947-1 Fitted with:

Mirror contact (not for microswitches)

Electronically compatible microswitch N/O

Suppressor circuit in actuating electronics

Electronically compatible microswitch N/C Interference immunity According to EN 60947-1 Lifespan, mechanical 10,000,000

Operations (DC operated) Operating frequency 5000 mechanical Operations/h (DC operated) Overvoltage category III

Pollution degree 3 Product category Safety contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 2.7 mΩ Shock resistance 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 6.9 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Mechanical, a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMS32-R23(RDC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.