

INDUSTRIAL COMPONENT DATA

**DILMS7-R23(110V50HZ,120V60HZ) 191733 Y7-191733 EATON
ELECTRIC Safety device, 3 pole + 2 N/O + 3 N/C, electro..**

Brand: EATON - MOELLER | Manufacturer Part Number: DILMS7-R23(110V50HZ,120V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMS7-R23(110V50HZ,120V60HZ)
Catalog number	Y7-191733
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-1AEEED3C28
Generated	2026-08-05

Product Overview

Safety device, 3 pole + 2 N/O + 3 N/C, electronically-compatible auxiliary contact, 3 kW/400V/AC3

DILMS7-R23(110V50HZ,120V60HZ)

Eaton Moeller® series DILMS Safety contactor, 380 V 400 V: 3 kW, 2 N/O, 3 NC, 110 V 50 Hz, 120 V 60 Hz, AC operation, Screw terminals, With mirror contact (not for microswitches).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMS Safety contactor Catalog Number 191733 Model Code

DILMS7-R23(110V50HZ,120V60HZ) EAN 4015081922468 Product Length/Depth 117 mm Product Height 69 mm Product

Width 45 mm Product Weight 0.288 kg Certifications IEC/EN 60947-4-1

VDE 0660

UL

CE

UL Category Control No.: NLDX

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096

CSA Class No.: 2411-03, 3211-04

IEC/EN 60947

UL 60947-4-1

CSA Catalog Notes Contacts according to EN 50012 General

Application Contactors for Motors Degree of protection IP20 Emitted interference According to EN 60947-1 Fitted with:

Mirror contact (not for microswitches)

Electronically compatible microswitch N/C

Electronically compatible microswitch N/O Interference immunity According to EN 60947-1 Lifespan, mechanical

10,000,000 Operations (AC operated) Operating frequency 9000 mechanical Operations/h (AC operated) Overvoltage

category III Pollution degree 3 Product category Safety contactors Protection Finger and back-of-hand proof, Protection

against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance

per pole 2.5 mΩ Shock resistance 3.4 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when

tabletop-mounted, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5.7 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMS7-R23(110V50HZ,120V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.