

INDUSTRIAL COMPONENT DATA

**DILMS80-22(110V50HZ,120V60HZ) 191728 Y7-191728 EATON
ELECTRIC Safety device, 3 pole + 2 N/O + 2 N/C, 37 kW/4..**

Brand: EATON - MOELLER | Manufacturer Part Number: DILMS80-22(110V50HZ,120V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMS80-22(110V50HZ,120V60HZ)
Catalog number	Y7-191728
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-84C4B9E9A5
Generated	2026-08-04

Product Overview

Safety device, 3 pole + 2 N/O + 2 N/C, 37 kW/400V/AC3

DILMS80-22(110V50HZ,120V60HZ)

Eaton Moeller® series DILMS Safety contactor, 380 V 400 V: 37 kW, 2 N/O, 2 NC, 110 V 50 Hz, 120 V 60 Hz, AC operation, Screw terminals, with mirror contact.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMS Safety contactor Catalog Number 191728 Model Code

DILMS80-22(110V50HZ,120V60HZ) EAN 4015081922413 Product Length/Depth 175 mm Product Height 170 mm Product

Width 90 mm Product Weight 2.31 kg Certifications UL File No.: E29096

CSA File No.: 012528

IEC/EN 60947-4-1

IEC/EN 60947

CSA Class No.: 2411-03, 3211-04

VDE 0660

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLDX

UL

CE

UL 60947-4-1

CSA Catalog Notes Contacts according to EN 50012 General

Application Contactors for Motors Degree of protection IP00 Emitted interference According to EN 60947-1 Fitted with:
Mirror contact Interference immunity According to EN 60947-1 Lifespan, mechanical 10,000,000 Operations (AC operated)
Operating frequency 3600 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product
category Safety contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from
front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA (with actuation of A1 - A2 by
the electronics with "0" signal) Resistance per pole 0.6 m Ω Shock resistance 5 g, N/C auxiliary contact, Mechanical,
according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms
10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMS80-22(110V50HZ,120V60HZ) with the required quantity to info@electricaonline.com or
use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.