

INDUSTRIAL COMPONENT DATA

**DILMS9-23(230V50HZ,240V60HZ) 191741 Y7-191741 EATON
ELECTRIC Contactor for 3ph three-phase capacitors, 20kVAR**

Brand: EATON - MOELLER | Manufacturer Part Number: DILMS9-23(230V50HZ,240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMS9-23(230V50HZ,240V60HZ)
Catalog number	Y7-191741
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-22EE970690
Generated	2026-08-06

Product Overview

Contactor for 3ph three-phase capacitors, 20kVAR

DILMS9-23(230V50HZ,240V60HZ)

Eaton Moeller® series DILMS Safety contactor, 380 V 400 V: 4 kW, 2 N/O, 3 NC, 230 V 50 Hz, 240 V 60 Hz, AC operation, Screw terminals, with mirror contact.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMS Safety contactor Catalog Number 191741 Model Code

DILMS9-23(230V50HZ,240V60HZ) EAN 4015081922543 Product Length/Depth 117 mm Product Height 69 mm Product

Width 45 mm Product Weight 0.288 kg Certifications CSA Class No.: 2411-03, 3211-04

UL 60947-4-1

VDE 0660

UL Category Control No.: NLDX

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-4-1

UL

UL File No.: E29096

CE

CSA

IEC/EN 60947 Catalog Notes Contacts according to EN 50012 General

Application Contactors for Motors Degree of protection IP20 Emitted interference According to EN 60947-1 Fitted with:
Mirror contact Interference immunity According to EN 60947-1 Lifespan, mechanical 10,000,000 Operations (AC operated)
Operating frequency 9000 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product
category Safety contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from
front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 2.5 m Ω ? Shock resistance 5.7 g,
N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms
3.4 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10
ms
7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
10 g, N/O main contact, Mechanical, according to IEC/EN 600...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMS9-23(230V50HZ,240V60HZ) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.