

INDUSTRIAL COMPONENT DATA

**DILMS95-22(230V50HZ,240V60HZ) 191750 Y7-191750 EATON
ELECTRIC Safety device, 3 pole + 2 N/O + 2 N/C, 45 kW/4..**

Brand: EATON - MOELLER | Manufacturer Part Number: DILMS95-22(230V50HZ,240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMS95-22(230V50HZ,240V60HZ)
Catalog number	Y7-191750
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-7DC3F6552C
Generated	2026-08-05

Product Overview

Safety device, 3 pole + 2 N/O + 2 N/C, 45 kW/400V/AC3

DILMS95-22(230V50HZ,240V60HZ)

Safety contactor, 380 V 400 V: 45 kW, 2 N/O, 2 NC, 230 V 50 Hz, 240 V 60 Hz, AC operation, Screw terminals, with mirror contact.

Safety contactor, Application: Contactors for Motors, Complete devices up to 170 A, Utilization category: AC-1:

Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Description: Auxiliary contact element connected non-detachably with basic device (manual activation not possible). , Rated operational current AC-3 380 V 400 V: $I_e = 95$ A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: $I_{th} = I_e = 130$ A, enclosed: $I_{th} = 100$ A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: $I_{th} = 275$ A, enclosed: $I_{th} = 250$ A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 30 kW, 380 V 400 V: P= 45 kW, 660 V 690 V: P= 75 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 16 kW, 380 V 400 V: P= 26 kW, 660 V 690 V: P= 35 kW, Contacts N/O = Normally op...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Safety contactor, 380 V 400 V: 45 kW, 2 N/O, 2 NC, 230 V 50 Hz, 240 V 60 Hz, AC operation, Screw terminals, with mirror contact. Safety contactor, Application: Contactors for Motors, Complete devices up to 170 A, Utilization category: AC-1:

Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Description: Auxiliary contact element connected non-detachably with basic device (manual activation not possible)., Rated operational current AC-3 380 V 400 V: $I_e = 95$ A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: $I_{th} = I_e = 130$ A, enclosed: $I_{th} = 100$ A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: $I_{th} = 275$ A, enclosed: $I_{th} = 250$ A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: $P = 30$ kW, 380 V 400 V: $P = 45$ kW, 660 V 690 V: $P = 75$ kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: $P = 16$ kW, 380 V 400 V: $P = 26$ kW, 660 V 690 V: $P = 35$ kW, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Instructions: Contacts to EN 50 012., with mirror contact., Voltage AC/DC: AC operation Delivery program Product range Safety contactors App...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMS95-22(230V50HZ,240V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.