

INDUSTRIAL COMPONENT DATA

DILMT50(RDC24) 190984 Y7-190984 EATON ELECTRIC Power Contactor close Connection screw 3 pole 50 A AC-3 RDC24

Brand: EATON - MOELLER | Manufacturer Part Number: DILMT50(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMT50(RDC24)
Catalog number	Y7-190984
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-6564B99F4A
Generated	2026-08-05

Product Overview

Power Contactor close; Connection screw; 3 pole; 50 A; AC-3; RDC24

DILMT50(RDC24)

Eaton Moeller® series DILMT Contactor, 3 pole, 380 V 400 V: 22 kW, 24 V DC, DC operation, Screw terminals
Contactor, Application: Contactors for Motors, Contactors up to 95 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Not suitable for motors with efficiency class IE3., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e = 50 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 70 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 15.5 kW, 380 V 400 V: P = 22 kW, 660 V 690 V: P = 30 kW, Can be combined with auxiliary contact: DILT-XHI01 (10), DILMT95-XHI11-SR, Voltage AC/DC: DC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMT Contactor Catalog Number 190984 Model Code DILMT50(RDC24) EAN 4015081912070 Product Length/Depth 108.1 mm Product Height 103.6 mm Product Width 55 mm Product Weight 0.776 kg Certifications EN 60335-1

GB14048

IEC/EN 60947 Catalog Notes Not suitable for motors with efficiency class IE3. Features & Functions

Fitted with: Varistor suppressor circuit Number Of Poles Three-pole General

Application Contactors for Motors Connection to SmartWire-DT No Degree of protection IP20 Frame size FS3 Lifespan, mechanical 5,000,000 Operations (DC operated) Operating frequency 3600 mechanical Operations/h (DC operated) Overvoltage category III Pollution degree 3 Product category Contactors Rated impulse withstand voltage (Uimp) 6000 V AC Used with DILMT95-XHI11-SR and DILT-XHI01(10) Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type DC Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Terminal capacities

Terminal capacity (solid) 2 x (0.75 - 2.5) mm²

1 x (0.75 - 2.5) mm²

1 x (2.5 - 25) mm², Main cables

2 x (2.5 - 16) mm², Main cables Terminal capacity (stranded) 1 x (2.5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMT50(RDC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.