

INDUSTRIAL COMPONENT DATA

DILMT65(230V50HZ/240V60HZ) 190964 Y7-190964 EATON ELECTRIC Power Contactor close Connection screw 3 pole 65

..

Brand: EATON - MOELLER | Manufacturer Part Number: DILMT65(230V50HZ/240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMT65(230V50HZ/240V60HZ)
Catalog number	Y7-190964
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-A2B6AAACD2
Generated	2026-08-06

Product Overview

Power Contactor close; Connection screw; 3 pole; 65 A; AC-3; 230 V 50 Hz, 240 V 60 Hz

DILMT65(230V50HZ/240V60HZ)

Eaton Moeller® series DILMT Contactor, 3 pole, 380 V 400 V: 30 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation, Screw terminals

Contactor, Application: Contactors for Motors, Contactors up to 95 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Not suitable for motors with efficiency class IE3., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e = 65 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 80 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 20 kW, 380 V 400 V: P = 30 kW, 660 V 690 V: P = 35 kW, Can be combined with auxiliary contact: DILT-XHI01 (10), DILMT95-XHI11-SR, Voltage AC/DC: AC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMT Contactor Catalog Number 190964 Model Code

DILMT65(230V50HZ/240V60HZ) EAN 4015081911875 Product Length/Depth 108.1 mm Product Height 103.6 mm Product

Width 55 mm Product Weight 0.776 kg Certifications EN 60335-1

GB14048

IEC/EN 60947 Catalog Notes Not suitable for motors with efficiency class IE3. Features & Functions

Number Of Poles Three-pole General

Application Contactors for Motors Connection to SmartWire-DT No Degree of protection IP20 Frame size FS3 Lifespan, mechanical 5,000,000 Operations (AC operated) Operating frequency 3600 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category Contactors Rated impulse withstand voltage (Uimp) 6000 V AC Used with DILMT95-XHI11-SR and DILT-XHI01(10) Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type AC Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Terminal capacities

Terminal capacity (solid) 2 x (0.75 - 2.5) mm²

1 x (0.75 - 2.5) mm²

1 x (2.5 - 25) mm², Main cables

2 x (2.5 - 16) mm², Main cables Terminal capacity (stranded) 1 x (2.5 - 25) mm²

2 x (2.5 - 16) mm²...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMT65(230V50HZ/240V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.