

INDUSTRIAL COMPONENT DATA

DILMT9(230V50HZ/240V60HZ) 190995 Y7-190995 EATON ELECTRIC Power Contactor close Connection screw 3 pole 9 A ..

Brand: EATON - MOELLER | Manufacturer Part Number: DILMT9(230V50HZ/240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMT9(230V50HZ/240V60HZ)
Catalog number	Y7-190995
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-CE50795D5D
Generated	2026-08-06

Product Overview

Power Contactor close; Connection screw; 3 pole; 9 A; AC-3; 230 V 50 Hz, 240 V 60 Hz

DILMT9(230V50HZ/240V60HZ)

Eaton Moeller® series DILMT Contactor, 3 pole, 380 V 400 V: 4 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation, Screw terminals

Contactor, Application: Contactors for Motors, Contactors up to 95 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e = 9 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 20 A, Max. rating for three-phase motors , 50 - 60 Hz AC-3 220 V 230 V: P = 2.5 kW, 380 V 400 V: P = 4 kW, Can be combined with auxiliary contact: DILT-XH1., Voltage AC/DC: AC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMT Contactor

Catalog Number 190995

Model Code DILMT9(230V50HZ/240V60HZ)

EAN 4015081912186

Product Length/Depth 77.5 mm

Product Height 70.1 mm

Product Width 27 mm

Product Weight 0.175 kg

Certifications EN 60335-1

GB14048

IEC/EN 60947

Catalog Notes Also tested according to AC-3e. Also suitable for motors with efficiency class IE3.

Features & Functions

Number of poles Three-pole

General information

Application Contactors for Motors

Connection to SmartWire-DT No

Degree of protection IP20

Frame size FS1

Lifespan, electrical 1,000,000 Operations (at 400V, AC-3)

Lifespan, mechanical 10,000,000 Operations (AC operated)

Operating frequency 3600 mechanical Operations/h (AC operated)

Overvoltage category III

Pollution degree 3

Product category Contactors

Rated impulse withstand voltage (Uimp) 6000 V AC

Used with DILT-XHI...

Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

Voltage type AC

Climatic environmental conditions

Ambient operating temperature - min -25 °C

Ambient operating temperature - max 55 °C

Ambient storage temperature - min -40 °C

Ambient storage temperature - max 80 °C

Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Terminal capacities

Terminal capacity (solid) 2 x (0.75 - 2.5) mm²

1 x (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMT9(230V50HZ/240V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.