

INDUSTRIAL COMPONENT DATA

DILMT95-XHI11-SR 190974 Y7-190974 EATON ELECTRIC

Auxiliary contact block 1 NO + 1 NC side Mounting

Connectio..

Brand: EATON - MOELLER | Manufacturer Part Number: DILMT95-XHI11-SR



Manufacturer	EATON - MOELLER
MPN / Reference	DILMT95-XHI11-SR
Catalog number	Y7-190974
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-84DA6D355C
Generated	2026-08-06

Product Overview

Auxiliary contact block; 1 NO + 1 NC; side Mounting; Connection screw; For contactors DILMT7...95

DILMT95-XHI11-SR

Eaton Moeller® series DILMT Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILMT40 - DILMT95

Auxiliary contact module, Function: for standard applications, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 1.9 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Mounting type: Side mounted, For use with: DILMT40..., DILMT50..., DILMT65..., DILMT80..., DILMT95..., Type: Side-mounting auxiliary contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMT Accessory Auxiliary contact module Catalog Number 190974 Model Code DILMT95-XHI11-SR EAN 4015081911974 Product Length/Depth 76.5 mm Product Height 15 mm Product Width 76.5 mm

Product Weight 0.055 kg Certifications IEC/EN 60947 Features & Functions

Functions For standard applications Number of poles Two-pole General

Model Top mounting Mounting method Side mounting Used with DILMT Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Terminal capacities

Terminal capacity (flexible with ferrule) 1 x (0.75 - 2.5) mm² Terminal capacity (solid) 1 x (0.75 - 2.5) mm², Screw terminals

Screwdriver size 2, Terminal screw, Pozidriv screwdriver Tightening torque 1.2 Nm, Screw terminals Electrical rating

Rated operational current (I_e) at AC-15, 220 V, 230 V, 240 V 4 A Rated operational current (I_e) at AC-15, 380 V, 400 V, 415

V 1.9 A Contacts

Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts

(normally open contacts) 1

ETIM for 190974 Low-voltage industrial controls and switchgear (EC000041)

Feature Name

Feature Value

Number of contacts as change-over contact (EF008257)

0

Number of contacts as normally open contact (EF008256)

1

Num...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMT95-XHI11-SR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.