


INDUSTRIAL COMPONENT DATA

DILP250/22(240V60HZ) 112713 XTCFA250L22B EATON ELECTRIC Contactor, 4p+2N/O+2N/C, 250A/AC1

Brand: EATON - MOELLER | Manufacturer Part Number: DILP250/22(240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILP250/22(240V60HZ)
Catalog number	XTCFA250L22B
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-A94FAE4DB6
Generated	2026-08-06

Product Overview

Contactor, 4p+2N/O+2N/C, 250A/AC1

Power Contactor; 4-pole + 2 NO + 2 NC; 250 A; AC-1; 240 V-60 Hz

Contactor, 4 pole, 250 A, 2 N/O, 2 NC, 240 V 60 Hz, AC operation, Screw terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Contactors up to 170A

Additional Product Information

Contactor, 4 pole, 250 A, 2 N/O, 2 NC, 240 V 60 Hz, AC operation, Screw terminals

Contactor, Application: Contactors for 4 pole electric consumers, Contactors larger than 200 A, 4 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, Connection technique: Screw terminals, Number of poles: 4 pole, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: $I_{th} = I_e = 250$ A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: $I_{th} = 700$ A, Rated operational current AC-1 220 V 230 V: $P = 45$ kW, 380 V 400 V: $P = 75$ kW, 660 V 690 V: $P = 110$ kW, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Voltage AC/DC: AC operation

Delivery program

Product range

Contactors

Application

Contactors for 4 pole electric consumers

Subrange

Contactors larger than 200 A, 4 pole

Utilization category

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

Connection technique

Screw terminals

Number of poles

4 pole

Rated operational current

AC-1

Conventional free air thermal current, 3 pole, 50 - 60 Hz

Open at 40 °C [$I_{th} = I_e$] 250 A

AC-1

Conventional free air thermal current, 3 pole, 50 - 60 Hz

Open at 55 °C [$I_{th} = I_e$] 230 A

AC-1

Conventional free air thermal current, 3 pole, 50 - 60 Hz

Open at 60 °C [$I_{th} = I_e$] 200 A

AC-1

Conventional free air thermal current, 1 pole

open [I_{th}] 700 A

Contacts

N/O = Normally open

2 N/O

N/C = Normally closed

2 NC

Contact sequence

For use

withDILP800-XHI...Actuating volt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILP250/22(240V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.