

INDUSTRIAL COMPONENT DATA

DILT-XHI20 190971 Y7-190971 EATON ELECTRIC Auxiliary contact block 2 NO front Mounting Connection screw For ..

Brand: EATON - MOELLER | Manufacturer Part Number: DILT-XHI20



Manufacturer	EATON - MOELLER
MPN / Reference	DILT-XHI20
Catalog number	Y7-190971
Category	Auxiliary contact block
Minimum order	10 Pcs
Document ID	EO-9499D43B4A
Generated	2026-08-05

Product Overview

Auxiliary contact block; 2 NO; front Mounting; Connection screw; For contactors DILMT7...95
DILT-XHI20

Auxiliary contact module, 2 pole, Ith= 10 A, 2 N/O, Front fixing, Screw terminals, DILAT, DILMT7 ... DILMT32
Auxiliary contact module, Function: for standard applications, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 1.9 A, Contacts N/O = Normally open: 2 N/O, Mounting type: Front fixing, For use with: DILAT..., DILMT7..., DILMT9..., DILMT12..., DILMT17..., DILMT25..., DILMT32..., Type: Front mounting auxiliary contact

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

EL-Nummer (Norway)4100431Auxiliary contact module, 2 pole, Ith= 10 A, 2 N/O, Front fixing, Screw terminals, DILAT, DILMT7 ... DILMT32Auxiliary contact module, Function: for standard applications, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 1.9 A, Contacts N/O = Normally open: 2 N/O, Mounting type: Front fixing, For use with: DILAT..., DILMT7..., DILMT9..., DILMT12..., DILMT17..., DILMT25..., DILMT32..., Type: Front mounting auxiliary contactDelivery program AccessoriesAuxiliary contact modulesFunctionfor standard applicationsNumber of poles2 poleConnection techniqueScrew terminalsRated operational currentConventional free air thermal current, 1 poleOpenat 60 °C [Ith]10 AAC-15220 V 230 V 240 V [Ie]4 AAC-15380 V 400 V 415 V [Ie]1.9 AContactsN/O = Normally open2 N/OMounting typeFront fixingContact sequenceFor use withDILAT...

DILMT7...

DILMT9...

DILMT12...

DILMT17...

DILMT25...

DILMT32...TypeFront mounting auxiliary contactTechnical data

GeneralStandardsIEC/EN 60947Lifespan, mechanicalAC operated [Operations]10 x 106Component lifespanat Ue= 230 V, AC-15, 3 A [Operations]1 x 106Maximum operating frequency [Operations/h]3600Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +55 °CAmbient temperatureAmbient temperature, storage- 40 - 80 °CDegree of ProtectionIP20Weight0.02 kgTerminal capacitiesScrew te...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILT-XHI20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.