

INDUSTRIAL COMPONENT DATA

MFD-80-X 284904 0004560922 EATON ELECTRIC Display, 80mm, 132x64pixels, monochrome, IP65 x, without logotype

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-80-X



Manufacturer	EATON - MOELLER
MPN / Reference	MFD-80-X
Catalog number	0004560922
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-387CCBAC97
Generated	2026-08-04

Product Overview

Display, 80mm, 132x64pixels, monochrome, IP65_x, without logotype

MFD-TITAN display; 80 mm; 132 x 64 pixels; Monochrome; IP65; Keyless; Unlabeled

Display and operating unit can be combined with power supply unit/CPU module MFD-CP8/CP10 or as remote text display with easy800 and easy800-SWD, monochrome display, 133x64pixels, with switchable backlight, without keypad, enclosure degree of protection IP65, removable silver front frame, without Eaton logotype, correspond to NEMA 4x protection class

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

EL-Nummer (Norway)4560922Display, 80mm, 132x64pixels, monochrome, IP65_x, without logotypeDisplay and operating unit can be combined with power supply unit/CPU module MFD-CP8/CP10 or as remote text display with easy800 and easy800-SWD, monochrome display, 133x64pixels, with switchable backlight, without keypad, enclosure degree of protection IP65, removable silver front frame, without Eaton logotype, correspond to NEMA 4x protection classDelivery program

Product rangeMulti-function-display MFD-TitanAccessoriesRemote text displaymonochrome display 132 × 64 pixels with switchable backlight

removable Titan front frame

Custom laser inscriptions possible with MFD-COMBINATION (article no. 2010801) productDisplaywith display, without keypadEaton logotypewithout Eaton company logotypeDegree of ProtectionIP65Connection typescrew terminalTechnical data

General Standards EN 61000-6-1/-2/-3/-4, IEC 60068-2-6, IEC 60068-2-27 Dimensions (W x H x D) 86.5 x 86.5 x 21.5 (with actuators) 86.5 x 86.5 x 20 (without actuators) mm Weight 0.13 kg Mounting 2 x 22.5 mm, display fixed with 2 fixing rings.

Wall thickness:

without top-hat rail (CPU) 1 - 6 mm

with top-hat rail 1 - 4 mm Power loss [P] 0 W Climatic environmental conditions Operating ambient temperature -25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °C Condensation Take appropriate measures to prevent condensation LCD display (clearly legible) -5 - 50 - (-10 to 0 when background lighting is switched on (continuous operation)) °C Storage -40...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-80-X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.