

INDUSTRIAL COMPONENT DATA

SRSD1NO 167375 EATON ELECTRIC Distribution board-light intensity switch, surface mounting light sensor

Brand: EATON - MOELLER | Manufacturer Part Number: SRSD1NO



Manufacturer	EATON - MOELLER
MPN / Reference	SRSD1NO
Catalog number	167375
Category	Twilight switch for distribution board
Minimum order	1 Pcs
Document ID	EO-DD2D4A6AD6
Generated	2026-07-29

Product Overview

Distribution board-light intensity switch, surface mounting light sensor

Distribution board-light intensity switch in 17.5 mm width, setting range 2-100 lux, separate body light sensor (IP54) with 1.5 m connecting cable, timed contact 16(10) A/250V~ on delay 20/80 sec. non-delayed threshold value and output LED displays.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

Distribution board-light intensity switch, surface mounting light sensor Eaton Catalog No. SRSD1NO EL-Nummer (Norway) 1456977 Distribution board-light intensity switch in 17.5 mm width, setting range 2-100 lux, separate body light sensor (IP54) with 1.5 m connecting cable, timed contact 16(10) A/250V~ on delay 20/80 sec. non-delayed threshold value and output LED displays. [Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0.6 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +50 °C 0 , Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Twilight switch for distribution board (EC001645) Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Twilight switch for distribution board ( [ACN363011]) Rated voltage 230 V Rated frequency 50 - 60 Hz Max. incandescent lamp load 2300 W Max. load fluorescent lamp 2300 VA Max. load

fluorescent lamp (Duo circuit) 2300 VA Max. load fluorescent lamp (parallel compensated) 400 VA Max. switching current (cos phi = 0.6) 0 A Rated switch current 16 A Adjustment range brightness value 2 - 100 lx With p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SRSD1NO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.