

INDUSTRIAL COMPONENT DATA

XVTL-MP/BF-10/6/16 114505 0002459920 EATON ELECTRIC

Distribution cabinet, HxWxD 1600x1000x600mm, IP55, bayab..

Brand: EATON - MOELLER | Manufacturer Part Number: XVTL-MP/BF-10/6/16



Manufacturer	EATON - MOELLER
MPN / Reference	XVTL-MP/BF-10/6/16
Catalog number	0002459920
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-6D514D7925
Generated	2026-08-06

Product Overview

Distribution cabinet, HxWxD=1600x1000x600mm, IP55, bayable

Frame with 2x depth mounting, rear panel, door, roof closed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Distribution cabinet, HxWxD=1600x1000x600mm, IP55 EL-Nummer (Norway) 0002459920 Frame with 2x depth mounting, rear panel, door, roof closed [Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure, free-standing [PV] 310 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Starting enclosure, free-standing [PV] 300 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Middle enclosure, free-standing [PV] 282 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV] 290 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Starting enclosure for wall mounting [PV] 275 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Middle enclosure for wall mounting [PV] 265 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure, free-standing [PV] 621 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVTL-MP/BF-10/6/16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.