

INDUSTRIAL COMPONENT DATA

XVTL-MP/BX/IC-12/4/16 114562 EATON ELECTRIC Distribution cabinet, HxWxD 1600x1200x400mm, IP55, bayable

Brand: EATON - MOELLER | Manufacturer Part Number: XVTL-MP/BX/IC-12/4/16



Manufacturer	EATON - MOELLER
MPN / Reference	XVTL-MP/BX/IC-12/4/16
Catalog number	114562
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-22EFE9B496
Generated	2026-08-06

Product Overview

Distribution cabinet, HxWxD=1600x1200x400mm, IP55, bayable

Frame, rear panel, door, roof closed, mounting plate 3 mm, multi-part bottom plates, lifting eyelets, double-bit lock

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Delivery programme Product range Control centres XVTL

Basic function Combination enclosures

Single unit/Complete unit Complete housing

Degree of Protection IP55 (with door and flange)

Description Fragment basic equipment

Including open cable entries top, prepared for F3A flange

Material Sheet steel 2 mm

Surface finish Polyester powder coating

Phosphated

RAL 7035, light grey

Colour RAL 7035, light grey

Information about equipment supplied including frame, sheet steel doors, back plate, bottom and top plate, mounting plate, lifting eyelets, cylinder lock and branding strip

Including support frame for the IVS mounting units

including insulating surround and mounted insulated support bracket

Without side walls

Width mm 1200

Height mm 1600

Depth mm 400

Technical data General

Standards IEC/EN 60439-1

IEC/EN 60439-3

IEC/EN 62208

Protection class 1

40 °C (intermittent maximum value)

35 °C (maximum value, 24 h average)

-5 °C (minimum value)

Installation conditions Indoor installation

Degree of Protection IP55 (with door and flange)

Relative humidity 50% (at 40°C)

Power loss

Max. admissible heat dissipation, ambient air temperature +35 °C W 614

Weight kg 119

Material characteristics

Material Sheet steel 2 mm

Surface treatment Painting, phosphated and polyester powder coating

Surface finish Polyester powder coating

Phosphated

RAL 7035, light grey

Colour RAL 7035, light grey

Material characteristics

Type Door Outside-supported doors with hidden hinges

Can be removed from 90°

From width....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVTL-MP/BX/IC-12/4/16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.