

INDUSTRIAL COMPONENT DATA

XVTL-MP/BX/IC-12/3/18 114576 2460170 EATON ELECTRIC
Distribution cabinet, HxWxD 1800x1200x300mm, IP55, bayab..

Brand: EATON - MOELLER | Manufacturer Part Number: XVTL-MP/BX/IC-12/3/18



Manufacturer	EATON - MOELLER
MPN / Reference	XVTL-MP/BX/IC-12/3/18
Catalog number	2460170
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-6610A9A065
Generated	2026-08-06

Product Overview

Distribution cabinet, HxWxD=1800x1200x300mm, IP55, bayable

Frame, rear panel, door, roof closed, mounting plate 3 mm, multi-part bottom plates, lifting eyelets, double-bit lock

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton xEffect xVtl empty enclosure Catalog Number 114576 Model Code XVTL-MP/BX/IC-12/3/18 EAN 4015081139767 Product Length/Depth 1200 mm Product Height 1800 mm Product Width 308.5 mm Product Weight 141 kg

Compliances RoHS conform Certifications IEC/EN 60439-3

IEC/EN 62208

IEC/EN 60439-1 Product specifications

Special features Type Control centres XVTL Features EMC-version

Connectable 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. 10.13 Mechanical function Meets the product standard's requirements.

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Not applicable. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Not applicable. 10.2.4

Resistance to ultra-violet (UV) radiation Not relevant to indoor installations. 10.2.5 Lifting Met; assembled and secured as

per the latest applicable instruction leaflet. 10.2.6 Mechanical impact IK10 10.2.7 Inscriptions Meets the product standard's requirements. 10.3 Degree of protection of assemblies IP55 10.4 Clearances and creepage distances...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVTL-MP/BX/IC-12/3/18 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.