

INDUSTRIAL COMPONENT DATA

XVTL-MP/BF-6/4/18 114510 Y7-114510 EATON ELECTRIC

Distribution cabinet, HxWxD 1800x600x400mm, IP55, bayable

Brand: EATON - MOELLER | Manufacturer Part Number: XVTL-MP/BF-6/4/18



Manufacturer	EATON - MOELLER
MPN / Reference	XVTL-MP/BF-6/4/18
Catalog number	Y7-114510
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-F6DB408718
Generated	2026-08-06

Product Overview

Distribution cabinet, HxWxD=1800x600x400mm, IP55, bayable

XVTL-MP/BF-6/4/18

Frame with 2x depth mounting, rear panel, door, roof closed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

Distribution cabinet, HxWxD=1800x600x400mm, IP55 Frame with 2x depth mounting, rear panel, door, roof closed Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure, free-standing [PV] 187 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Starting enclosure, free-standing [PV] 177 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Middle enclosure, free-standing [PV] 155 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure for wall mounting [PV] 167 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Starting enclosure for wall mounting [PV] 149 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Middle enclosure for wall mounting [PV] 135 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure, free-standing [PV] 375 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35

degrees in top of the enclosure, calculated a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVTL-MP/BF-6/4/18 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.