

INDUSTRIAL COMPONENT DATA

XVTL-MP/BX/IC-4/3/20 114580 EATON ELECTRIC Distribution cabinet, HxWxD 2000x400x300mm, IP55, bayable

Brand: EATON - MOELLER | Manufacturer Part Number: XVTL-MP/BX/IC-4/3/20



Manufacturer	EATON - MOELLER
MPN / Reference	XVTL-MP/BX/IC-4/3/20
Catalog number	114580
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-1749C1CF0F
Generated	2026-08-06

Product Overview

Distribution cabinet, HxWxD=2000x400x300mm, IP55, bayable

Frame, rear panel, door, roof closed, mounting plate 3 mm, multi-part bottom plates, lifting eyelets, double-bit lock

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton xEffect xVtl empty enclosure Catalog Number 114580 Model Code XVTL-MP/BX/IC-4/3/20 EAN 4015081139804 Product Length/Depth 425 mm Product Height 2000 mm Product Width 308.5 mm Product Weight 80 kg
Compliances RoHS conform Certifications IEC/EN 60439-1

IEC/EN 62208

IEC/EN 60439-3 Product specifications

Special features Type Control centres XVTL Features Connectable

EMC-version 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. 10.13 Mechanical function Meets the product standard's requirements. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Not applicable. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Not applicable. 10.2.4 Resistance to ultra-violet (UV) radiation Not relevant to indoor installations. 10.2.5 Lifting Met; assembled and

secured as per the latest applicable instruction leaflet. 10.2.6 Mechanical impact IK10 10.2.7 Inscriptions Meets the product standard's requirements. 10.3 Degree of protection of assemblies IP55 10.4 Clearances and creepage distances Is...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVTL-MP/BX/IC-4/3/20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.