

INDUSTRIAL COMPONENT DATA

XVTL-MP/BX/IC-6/3/20 114585 0002460003 EATON ELECTRIC

Distribution cabinet, HxWxD 2000x600x300mm, IP55, baya..

Brand: EATON - MOELLER | Manufacturer Part Number: XVTL-MP/BX/IC-6/3/20



Manufacturer	EATON - MOELLER
MPN / Reference	XVTL-MP/BX/IC-6/3/20
Catalog number	0002460003
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-C56088D7F3
Generated	2026-08-06

Product Overview

Distribution cabinet, HxWxD=2000x600x300mm, IP55, bayable

Frame, rear panel, door, roof closed, mounting plate 3 mm, multi-part bottom plates, lifting eyelets, double-bit lock

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Distribution cabinet, HxWxD=2000x600x600mm, IP55 EL-Nummer (Norway) 0002460003 Frame, rear panel, door, roof closed, mounting plate 3 mm, multi-part bottom plates, lifting eyelets, double-bit lock [Delivery program

Product range Control centres XVTL Basic function Combination enclosures Single unit/Complete unit Complete housing

Degree of Protection IP55 (with door and flange) Description Fragment basic equipment

Including open cable entries top, prepared for F3A flange Material Sheet steel 2 mm Surface finish Polyester powder coating

Phosphated

RAL 7035, light grey Colour light gray (RAL 7035) Information about equipment supplied including frame, sheet steel doors, back plate, bottom and top plate, mounting plate, lifting eyelets, cylinder lock and branding strip

Including support frame for the IVS mounting units

including insulating surround and mounted insulated support bracket

Without side walls Width 600 mm Height 2000 mm Depth 600 mm , Technical data

General Standards IEC/EN 60439-1

IEC/EN 60439-3

IEC/EN 62208 Protection class 1 40 °C (intermittent maximum value)

35 °C (maximum value, 24 h average)

-5 °C (minimum value) Installation conditions Indoor installation Degree of Protection IP55 (with door and flange) Relative humidity 50% (at 40°C) Power lossMax. admissible heat dissipation, ambient air temperature +35 °C 505 W Weight 89 kg Material characteristics Material Sheet steel 2 mm Surface treatment Painting, phosphated and polyester powder coating Surface finish P...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVTL-MP/BX/IC-6/3/20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.