


INDUSTRIAL COMPONENT DATA

DIULEEM/21/MV(110V50HZ,120V60HZ) 051668 EATON ELECTRIC Reversing contactor combination, 3p, +2S free, 3kW/40..

Brand: EATON - MOELLER | Manufacturer Part Number: DIULEEM/21/MV(110V50HZ,120V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DIULEEM/21/MV(110V50HZ,120V60HZ)
Catalog number	051668
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-6D849B5C34
Generated	2026-08-06

Product Overview

Reversing contactor combination, 3p, +2S free, 3kW/400V/AC3

DIULEEM/21/MV(110V50HZ,120V60HZ)

Reversing contactor combination, 380 V 400 V: 3 kW, 110 V 50 Hz, 120 V 60 Hz, AC operation

Reversing contactor combination, Application: Contactor combinations for starting motors with two directions of rotation, Accessories: DIUL reversing combinations, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Rated operational current AC-3 380 V 400 V: I_e= 6.6 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 1.5 kW, 380 V 400 V: P= 3 kW, 660 V 690 V: P= 3 kW, Actuating voltage: 110 V 50 Hz, 120 V 60 Hz, Voltage AC/DC: AC operation, Notes: Also suitable for motors with efficiency class IE3. , IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Reversing contactor combination, 380 V 400 V: 3 kW, 110 V 50 Hz, 120 V 60 Hz, AC operation Reversing contactor combination, Application: Contactor combinations for starting motors with two directions of rotation, Accessories: DIUL reversing combinations, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Rated operational current AC-3 380 V 400 V: I_e= 6.6 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 1.5 kW, 380 V 400 V: P= 3 kW, 660 V 690 V: P= 3

kW, Actuating voltage: 110 V 50 Hz, 120 V 60 Hz, Voltage AC/DC: AC operation, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging. Delivery program

Product range Contactor combinations Application Contactor combinations for starting motors with two directions of rotation Accessories DIUL reversing combinations Utilization category NAC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Notes Also suitable for motors with efficiency class IE3.

IE3-ready devices are identified by the logo on their packaging. Rated operational current [I_e] AC-3380 V 400 V [I_e] 6.6 A Max. rating for three-phase motors, 50 - 60 Hz AC-3220 V 230 V [P] 1.5 kW AC-3380 V 400 V [P] 3 kW AC-3660 V 690 V [P] 3 kW AC-4220 V 230 V [P] 1.1 kW AC-4380 V 400 V [P] 2.2 kW AC-4660 V 690 V [P] 2.2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DIULEEM/21/MV(110V50HZ,120V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.