

INDUSTRIAL COMPONENT DATA

DIULEEM/21/MV(230V50HZ,240V60HZ) 051664 Y7-51664 EATON ELECTRIC Reversing contactor combination, 3p, +2S fre..

Brand: EATON - MOELLER | Manufacturer Part Number: DIULEEM/21/MV(230V50HZ,240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DIULEEM/21/MV(230V50HZ,240V60HZ)
Catalog number	Y7-51664
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-4934F23BEB
Generated	2026-08-06

Product Overview

DIULEEM/21/MV(230V50HZ,240V60HZ)

Eaton Moeller® series DIULE Reversing contactor combination, 380 V 400 V: 3 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation

Reversing contactor combination, Application: Contactor combinations for starting motors with two directions of rotation, Accessories: DIUL reversing combinations, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Rated operational current AC-3 380 V 400 V: I_e= 6.6 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 1.5 kW, 380 V 400 V: P= 3 kW, 660 V 690 V: P= 3 kW, Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, Voltage AC/DC: AC operation, Notes: Also suitable for motors with efficiency class IE3. , IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DIULE contactor combination Catalog Number 051664 Model Code DIULEEM/21/MV(230V50HZ,240V60HZ) EAN 4015080516644 Product Length/Depth 94 mm Product Height 61 mm Product Width 90 mm Product Weight 0.445 kg Certifications UL 508
CSA File No.: 012528

UL

IEC/EN 60947-4-1

UL File No.: E29096

UL Category Control No.: NLDX

CSA Class No.: 3211-04

CSA-C22.2 No. 14-05

CE

CSA Catalog Notes IE3-fähige Geräte sind mit dem Logo auf der Verpackung gekennzeichnet. Features & Functions

Features Mechanical interlock Functions Reversing safety General

Application Contactor combinations for starting motors with two directions of rotation Product category Contactor combinations Suitable for Also motors with efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Electrical Rating

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 6.6 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415

V 6.6 A Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 6.6 A Rated operational power at AC-3, 380/400 V, 50

Hz 3 kW Rated operational power at AC-4, 220/230 V, 50 Hz 1.1 kW Rated operational power at AC-4, 660/690 V, 50 Hz

2.2 kW Magnet system

Duty factor 100 % Rated con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DIULEEM/21/MV(230V50HZ,240V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.