

INDUSTRIAL COMPONENT DATA

DIULM115/11(RAC120) 239857 XTCR115G11A EATON ELECTRIC Reversing contactor combination, 3p, 55kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DIULM115/11(RAC120)



Manufacturer	EATON - MOELLER
MPN / Reference	DIULM115/11(RAC120)
Catalog number	XTCR115G11A
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-55C72C2D25
Generated	2026-08-06

Product Overview

Reversing contactor combination, 3p, 55kW/400V/AC3

Combination of contactors Inverter; Connection screw; 3 pole; 115; 55 kW; 400 V; AC-3; RAC120

Reversing contactor combination, Application: Contactor combinations for starting motors with two directions of rotation, Accessories: DIUL reversing combinations, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Rated operational current AC-3 380 V 400 V: I_e= 115 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 37 kW, 380 V 400 V: P= 55 kW, 660 V 690 V: P= 90 kW, Actuating voltage: 120 V AC, Voltage AC/DC: AC operation, Notes: Also suitable for motors with efficiency class IE3. , IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

Reversing contactor combination, 3p, 55kW/400V/AC3 Alternate Catalog No. XTCR115G11A Reversing contactor combination, Application: Contactor combinations for starting motors with two directions of rotation, Accessories: DIUL reversing combinations, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Rated operational current AC-3 380 V 400 V: I_e= 115 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 37 kW, 380 V 400 V: P= 55 kW, 660 V 690 V: P= 90 kW, Actuating voltage: 120 V AC, Voltage AC/DC: AC operation, Notes: Also suitable for motors with efficiency class IE3.,

IE3-ready devices are identified by the logo on their packaging. [Delivery program

Product range Contactor combinations Application Contactor combinations for starting motors with two directions of rotation

Accessories DIUL reversing combinations Utilization category NAC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Notes Also suitable for motors with efficiency class IE3.

IE3-ready devices are identified by the logo on their packaging. Rated operational current [Ie] AC-3380 V 400 V [Ie] 115 A Max. rating for three-phase motors, 50 - 60 Hz AC-3220 V 230 V [P] 37 kW AC-3380 V 400 V [P] 55 kW AC-3660 V 690 V [P] 90 kW AC-4220 V 230 V [P] 17 kW AC-4380 V 400 V [P] 28 kW AC-4660 V 690 V [...]

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DIULM115/11(RAC120) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.