

INDUSTRIAL COMPONENT DATA

DM1-127D8NB-S20S-EM 3-5048-003A EATON ELECTRIC

DM1-127D8NB-S20S-EM

Brand: EATON - MOELLER | Manufacturer Part Number: DM1-127D8NB-S20S-EM

Manufacturer	EATON - MOELLER
MPN / Reference	DM1-127D8NB-S20S-EM
Catalog number	3-5048-003A
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-C6F4C59553
Generated	2026-08-06

Product Overview

DM1-127D8NB-S20S-EM

Variable frequency drive, 230 V AC, 1-phase, 7.8 A, 1.5 kW, IP20/NEMA0, 7-digital display assembly, Setpoint potentiometer, Brake chopper, STO (Safe Torque Off, SIL2, PLd Cat 3)

Variable frequency drive DM1, Mains voltage: 200 - 240 V AC, 1-phase, Nominal output current: 7.8 A, Output at linear load at rated output voltage - max: 1.5 kW, fitted with: IGBT inverter, 7-digital display assembly, Setpoint potentiometer, Brake chopper, Internal DC link, DC link choke, Breaking resistance, Control unit, PC connection, Frame Size: FS2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Power XL Frequency Converters
--------------	---

Additional Product Information

General specifications

Product Name Eaton DM1 Variable frequency drive Catalog Number 3-5048-003A Model Code DM1-127D8NB-S20S-EM

EAN 4015081980611 Product Length/Depth 180 mm Product Height 220 mm Product Width 109 mm Product Weight 2.6 kg

Certifications CSA-C22.2 No. 274-17

CSA-C22.2 No. 274-13

UkrSEPRO

IEC/EN 61800-5-1

Certified by UL for use in Canada

UL File No.: E134360

EAC

CUL

IEC/EN 61800-2

C-Tick

CE marking

UL

UL report applies to both US and Canada

CE

IEC/EN61800-3

UL 508C

UL Listed

IEC/EN61800-5

RoHS, ISO 9001

UL Category Control No.: NMMS, NMMS7

IEC/EN 61800-3 General

Air volume capacity 42 m³/h Communication interface Modbus RTU, built in

Ethernet IP, built in

DeviceNet, optional

CANopen®, optional

Modbus TCP, built in

SmartWire-DT, optional

BACnet TCP

BACnet MS/TP, built in

PROFIBUS, optional Connection to SmartWire-DT In conjunction with DXG-NET-SWD SmartWire DT module

Yes Degree of protection IP20

NEMA Other Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Environmental class 3C2,

3S2 (Air quality) Features Parameterization: Power Xpert inControl

Parameterization: Fieldbus

Temperature-controlled fan

Parameterization: Keypad Fitted with: IGBT inverter

7-digital display assembly

Setpoint potentiometer

Brake chopper

Internal DC link

Breaking resistance

Control unit

PC connection Frame size FS2 Mounting position Vertical Number of slots 1 (expansion) Overvoltage category III Pollution degree 2 Product Category Variable frequency dri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DM1-127D8NB-S20S-EM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.