

INDUSTRIAL COMPONENT DATA

**DM1-324D8NB-S20S-EM 3-5002-007A EATON ELECTRIC
DM1-324D8NB-S20S-EM**

Brand: EATON - MOELLER | Manufacturer Part Number: DM1-324D8NB-S20S-EM



Manufacturer	EATON - MOELLER
MPN / Reference	DM1-324D8NB-S20S-EM
Catalog number	3-5002-007A
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-239BCD9E5C
Generated	2026-08-04

Product Overview

DM1-324D8NB-S20S-EM

Variable frequency drive, 230 V AC, 3-phase, 4.8 A, 1.1 kW, IP20/NEMA0, 7-digital display assembly, Setpoint potentiometer, Brake chopper, STO (Safe Torque Off, SIL2, PLd Cat 3)

Variable frequency drive DM1, Mains voltage: 200 - 240 V AC, 3-phase, Nominal output current: 4.8 A, Output at linear load at rated output voltage - max: 0.75 kW, fitted with: Setpoint potentiometer, Brake chopper, 7-digital display assembly, DC link choke, Internal DC link, IGBT inverter, Breaking resistance, Control unit, PC connection, Frame Size: FS1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Power XL Frequency Converters
--------------	---

Additional Product Information

General specifications

Product Name Eaton DM1 Variable frequency drive Catalog Number 3-5002-007A Model Code DM1-324D8NB-S20S-EM
EAN 4015081980727 Product Length/Depth 180 mm Product Height 152 mm Product Width 72 mm Product Weight 1.2 kg
Certifications UL 508C

UL report applies to both US and Canada

IEC/EN61800-5

IEC/EN 61800-5-1

EAC

C-Tick

CSA-C22.2 No. 274-13

CE marking
UkrSEPRO
CSA-C22.2 No. 274-17
CE
CUL
RoHS, ISO 9001
UL File No.: E134360
UL Category Control No.: NMMS, NMMS7
IEC/EN61800-3
UL
IEC/EN 61800-3
UL Listed
Certified by UL for use in Canada
IEC/EN 61800-2 General
Air volume capacity 26 m³/h Communication interface BACnet MS/TP, built in
Modbus TCP, built in
Ethernet IP, built in
BACnet TCP
DeviceNet, optional
SmartWire-DT, optional
Modbus RTU, built in
CANopen®, optional
PROFIBUS, optional Connection to SmartWire-DT In conjunction with DXG-NET-SWD SmartWire DT module
Yes Degree of protection IP20
NEMA Other Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Environmental class 3C2, 3S2 (Air quality) Features Parameterization: Power Xpert inControl
Temperature-controlled fan
Parameterization: Fieldbus
Parameterization: Keypad Fitted with: Setpoint potentiometer
Brake chopper
7-digital display assembly
Internal DC link
IGBT inverter
Breaking resistance
Control unit
PC connection Frame size FS1 Mounting position Vertical Number of slots 1 (expansion) Overvoltage category III Pollution degree 2 Product Category Variable frequency driv...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DM1-324D8NB-S20S-EM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.