

INDUSTRIAL COMPONENT DATA

DM1-341D5NB-S20S-EM 3-5010-005A EATON ELECTRIC

DM1-341D5NB-S20S-EM

Brand: EATON - MOELLER | Manufacturer Part Number: DM1-341D5NB-S20S-EM



Manufacturer	EATON - MOELLER
MPN / Reference	DM1-341D5NB-S20S-EM
Catalog number	3-5010-005A
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-E38FCA8872
Generated	2026-08-04

Product Overview

DM1-341D5NB-S20S-EM

Variable frequency drive, 400 V AC, 3-phase, 1.5 A, 0.55 kW, IP20/NEMA0, 7-digital display assembly, Setpoint potentiometer, Brake chopper, STO (Safe Torque Off, SIL2, PLd Cat 3)

Variable frequency drive DM1, Mains voltage: 380 - 480 V AC, 3-phase, Nominal output current: 1.5 A, Output at linear load at rated output voltage - max: 0.37 kW, fitted with: Setpoint potentiometer, IGBT inverter, Brake chopper, Internal DC link, 7-digital display assembly, DC link choke, Breaking resistance, Control unit, PC connection, Frame Size: FS1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Power XL Frequency Converters
--------------	---

Additional Product Information

General specifications

Product Name Eaton DM1 Variable frequency drive Catalog Number 3-5010-005A Model Code DM1-341D5NB-S20S-EM
EAN 4015081980888 Product Length/Depth 180 mm Product Height 152 mm Product Width 72 mm Product Weight 1.2 kg
Certifications UL report applies to both US and Canada

IEC/EN61800-5

UL Listed

UL 508C

UL File No.: E134360

IEC/EN 61800-5-1

CE

IEC/EN 61800-2
IEC/EN 61800-3
IEC/EN61800-3
Certified by UL for use in Canada
UL Category Control No.: NMMS, NMMS7
CSA-C22.2 No. 274-17
RoHS, ISO 9001
CUL
UkrSEPRO
C-Tick
EAC
UL
CE marking
CSA-C22.2 No. 274-13 General
Air volume capacity 26 m³/h Communication interface DeviceNet, optional
Ethernet IP, built in
CANopen®, optional
Modbus TCP, built in
BACnet MS/TP, built in
BACnet TCP
PROFIBUS, optional
SmartWire-DT, optional
Modbus RTU, built in Connection to SmartWire-DT In conjunction with DXG-NET-SWD SmartWire DT module
Yes Degree of protection IP20
NEMA Other Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Environmental class 3C2, 3S2 (Air quality) Features Temperature-controlled fan
Parameterization: Power Xpert inControl
Parameterization: Fieldbus
Parameterization: Keypad Fitted with: Setpoint potentiometer
IGBT inverter
Brake chopper
Internal DC link
7-digital display assembly
Breaking resistance
Control unit
PC connection Frame size FS1 Mounting position Vertical Number of slots 1 (expansion) Overvoltage category III Pollution degree 2 Product Category Variable frequency driv...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DM1-341D5NB-S20S-EM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.