

INDUSTRIAL COMPONENT DATA

**DM1-345D6NB-N20B-EM 3-5026-008A EATON ELECTRIC
DM1-345D6NB-N20B-EM**

Brand: EATON - MOELLER | Manufacturer Part Number: DM1-345D6NB-N20B-EM



Manufacturer	EATON - MOELLER
MPN / Reference	DM1-345D6NB-N20B-EM
Catalog number	3-5026-008A
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-E9F8E8CDC5
Generated	2026-08-06

Product Overview

DM1-345D6NB-N20B-EM

Variable frequency drive, 400 V AC, 3-phase, 5.6 A, 2.2 kW, IP20/NEMA0, Brake chopper

Variable frequency drive DM1, Mains voltage: 380 - 480 V AC, 3-phase, Nominal output current: 5.6 A, Output at linear load at rated output voltage - max: 2.2 kW, fitted with: Internal DC link, DC link choke, IGBT inverter, Brake chopper, Breaking resistance, PC connection, Frame Size: FS1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DM1 Variable frequency drive Catalog Number 3-5026-008A Model Code DM1-345D6NB-N20B-EM
EAN 4015081980338 Product Length/Depth 180 mm Product Height 152 mm Product Width 72 mm Product Weight 1.2 kg

Certifications UL 508C

Certified by UL for use in Canada

IEC/EN61800-5

IEC/EN 61800-3

EAC

RoHS, ISO 9001

CSA-C22.2 No. 274-17

UL

CE
CSA-C22.2 No. 274-13
UL Category Control No.: NMMS, NMMS7
IEC/EN 61800-2
IEC/EN 61800-5-1
CUL
C-Tick
UkrSEPRO
UL File No.: E134360
UL Listed
UL report applies to both US and Canada
IEC/EN61800-3
CE marking General
Air volume capacity 26 m³/h Communication interface Modbus RTU, built in
SmartWire-DT, optional
DeviceNet, optional
PROFIBUS, optional
CANopen®, optional Connection to SmartWire-DT Yes
In conjunction with DXG-NET-SWD SmartWire DT module Degree of protection IP20
NEMA Other Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Environmental class 3C2, 3S2 (Air quality) Features Parameterization: Fieldbus
Parameterization: Keypad
Temperature-controlled fan
Parameterization: Power Xpert inControl Fitted with: Internal DC link
IGBT inverter
Brake chopper
Breaking resistance
PC connection Frame size FS1 Mounting position Vertical Number of slots 1 (expansion) Overvoltage category III Pollution degree 2 Product Category Variable frequency drives Protection Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4) Radio interference class C2, C3: depending on....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DM1-345D6NB-N20B-EM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.