

INDUSTRIAL COMPONENT DATA

DMM-100/3 199532 Y8-199532 EATON ELECTRIC DMM-100/3

Brand: EATON - MOELLER | Manufacturer Part Number: DMM-100/3



Manufacturer	EATON - MOELLER
MPN / Reference	DMM-100/3
Catalog number	Y8-199532
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-85521F2C13
Generated	2026-08-01

Product Overview

DMM-100/3

Switch-disconnector, DMM, 100 A, 3 pole, With black rotary handle and drive shaft

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

Switch-disconnector, DMM, 100 A, 3 pole, With black rotary handle and drive shaftSwitch-disconnector, Product range:
Switch-disconnector, Main switch, maintenance switch, Part group reference: DMM, With black rotary handle and drive
shaft, Notes: visible contacts, Information about equipment supplied: auxiliary contact fitted by user., including connection
materials, 3 pole, Degree of Protection: IP20, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 59 kW,
Rated uninterrupted current: I_u = 100 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector
according to IEC/EN 60947-3Delivery program

Product rangeSwitch-disconnector

Main switch

maintenance switchPart group referenceDMMWith black rotary handle and drive shaftInformation about equipment
suppliedauxiliary contact fitted by user.Number of poles3 poleAuxiliary contacts0 N/O0 N/CNotes1 padlock, ? 5 mmLocking
facilityLockable in the 0 (Off) positionDegree of ProtectionIP20Designsurface mountingContact sequenceMotor rating
AC-23A, 50 - 60 Hz [P]400 V [P]55 kWRated uninterrupted current [I_u]100 ANote on rated uninterrupted current !uRated
uninterrupted current I_{uis} specified for max. cross-section.Connection techniqueVertical connectionTechnical data
GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204
Switch-disconnector according to IEC/EN 60947-3Ambient temperatureOperation [?]-25 - +55 °CAmbient

temperatureStorage [?]-30 - +80 °COvervoltage category/pollution degreeIII/3Rated impulse w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMM-100/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.