

INDUSTRIAL COMPONENT DATA

DMM-125/3-SK 6083336 Y8-6083336 EATON ELECTRIC

Switch-disconnector, 3 pole, 125 A, Without rotary handle and..

Brand: EATON - MOELLER | Manufacturer Part Number: DMM-125/3-SK



Manufacturer	EATON - MOELLER
MPN / Reference	DMM-125/3-SK
Catalog number	Y8-6083336
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-617B088A9E
Generated	2026-08-04

Product Overview

Switch-disconnector, 3 pole, 125 A, Without rotary handle and drive shaft, surface mounting

DMM-125/3-SK

Eaton DMM Switch-disconnector, DMM, 125 A, 3 pole, Stop Function optional, Without rotary handle and drive shaft

Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMM, Stop Function: optional, Without rotary handle and drive shaft, Notes: visible contacts, Information about equipment supplied: auxiliary contact fitted by user., including connection materials, 3 pole, Degree of Protection: IP20, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 59 kW, Rated uninterrupted current: I_u = 125 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DMM Switch-disconnector Catalog Number 6083336 Model Code DMM-125/3-SK EAN

8711426108721 Product Length/Depth 120 mm Product Height 150 mm Product Width 120 mm Product Weight 0.125 kg

Certifications IEC/EN 60947-3

EAC

VDE 0660

RoHS

KEMA

CE

IEC/EN 60204

Lloyds

IEC/EN 60947 Features & Functions

Features Version as main switch

Version as maintenance-/service switch Functions Optional Stop Function Number of poles Three-pole General

Accessories Actuator color Other Actuator type Other Degree of protection NEMA Other Degree of protection (front side)

IP20 Lifespan, mechanical 10,000 Operations Mounting method Surface mounting Mounting position As required

Overvoltage category III Pollution degree 3 Product Category Main switch

Switch-disconnector

Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Ground mounting

Distribution board installation Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 6 - 70 mm², flexible with ferrules to DIN 46228 Stripping length (main cable) 21 mm Tightening torque 7 Nm, Screw terminals Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) 10000 A Rated breaking capacity at 500 V (cos phi to IEC 60947-3) 528 A Rated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMM-125/3-SK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.