

INDUSTRIAL COMPONENT DATA

DMM-160/3 6093347 Y8-6093347 EATON ELECTRIC

Switch-disconnector, 3 pole, 160 A, With black rotary handle and..

Brand: EATON - MOELLER | Manufacturer Part Number: DMM-160/3



Manufacturer	EATON - MOELLER
MPN / Reference	DMM-160/3
Catalog number	Y8-6093347
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-50DDC8F666
Generated	2026-08-04

Product Overview

Switch-disconnector, 3 pole, 160 A, With black rotary handle and drive shaft, surface mounting
DMM-160/3

Eaton DMM Switch-disconnector, DMM, 160 A, 3 pole, With black rotary handle and drive shaft

Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMM, With black rotary handle and drive shaft, Notes: visible contacts, Information about equipment supplied: auxiliary contact fitted by user., including connection materials, 3 pole, Degree of Protection: IP20, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 80 kW, Rated uninterrupted current: I_u = 160 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DMM Switch-disconnector Catalog Number 6093347 Model Code DMM-160/3 EAN 8711426208896

Product Length/Depth 155 mm Product Height 115 mm Product Width 137 mm Product Weight 0.9 kg Certifications IEC/EN 60204

CE

Lloyds

RoHS

VDE 0660

EAC

IEC/EN 60947

IEC/EN 60947-3

KEMA Features & Functions

Features Version as main switch

Version as maintenance-/service switch Fitted with: Black rotary handle and drive shaft Number of poles Three-pole General

Accessories Actuator color Black Actuator type Short thumb-grip Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 10,000 Operations Mounting method Surface mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Main switch

Switch-disconnector

Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Intermediate mounting

Ground mounting

Distribution board installation Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 6 - 70 mm², flexible with ferrules to DIN 46228 Stripping length (main cable) 21 mm Tightening torque 7 Nm, Screw terminals Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) 10000 A Rated breaking capacity a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMM-160/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.