

INDUSTRIAL COMPONENT DATA

DMM-160/3-SK 6085416 Y8-6085416 EATON ELECTRIC

Switch-disconnector, 3 pole, 160 A, Without rotary handle and..

Brand: EATON - MOELLER | Manufacturer Part Number: DMM-160/3-SK



Manufacturer	EATON - MOELLER
MPN / Reference	DMM-160/3-SK
Catalog number	Y8-6085416
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-83B94917EF
Generated	2026-08-05

Product Overview

Switch-disconnector, 3 pole, 160 A, Without rotary handle and drive shaft, surface mounting

DMM-160/3-SK

Eaton DMM Switch-disconnector, DMM, 160 A, 3 pole, Stop Function optional, Without rotary handle and drive shaft

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DMM Switch-disconnector Catalog Number 6085416 Model Code DMM-160/3-SK EAN

8711426426894 Product Length/Depth 120 mm Product Height 150 mm Product Width 120 mm Product Weight 0.875 kg

Certifications KEMA

RoHS

IEC/EN 60947-3

Lloyds

IEC/EN 60204

IEC/EN 60947

VDE 0660

EAC

CE Features & Functions

Features Version as main switch

Version as maintenance-/service switch Functions Optional Stop Function Number of poles Three-pole General

Accessories Actuator color Other Actuator type Other Degree of protection NEMA Other Degree of protection (front side)

IP20 Lifespan, mechanical 10,000 Operations Mounting method Surface mounting Mounting position As required

Overvoltage category III Pollution degree 3 Product Category Main switch

Switch-disconnector

Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Ground mounting

Intermediate mounting

Distribution board installation Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 6 - 70 mm², flexible with ferrules to DIN 46228 Stripping length (main cable) 21 mm Tightening torque 7 Nm, Screw terminals Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) 10000 A Rated breaking capacity at 500 V (cos phi to IE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMM-160/3-SK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.