

INDUSTRIAL COMPONENT DATA

DMM-160/4 6093346 Y8-6093346 EATON ELECTRIC

Switch-disconnector, 4 pole, 160 A, With black rotary handle and..

Brand: EATON - MOELLER | Manufacturer Part Number: DMM-160/4



Manufacturer	EATON - MOELLER
MPN / Reference	DMM-160/4
Catalog number	Y8-6093346
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-8972E8A05A
Generated	2026-08-04

Product Overview

Switch-disconnector, 4 pole, 160 A, With black rotary handle and drive shaft, surface mounting

DMM-160/4

Eaton DMM Switch-disconnector, DMM, 160 A, 4 pole, With black rotary handle and drive shaft

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton DMM Switch-disconnector Catalog Number 6093346 Model Code DMM-160/4 EAN 8711426741881

Product Length/Depth 155 mm Product Height 115 mm Product Width 137 mm Product Weight 0.975 kg Certifications

Lloyds

CE

RoHS

IEC/EN 60947-3

EAC

IEC/EN 60204

IEC/EN 60947

KEMA

VDE 0660 Features & Functions

Features Version as maintenance-/service switch

Version as main switch Fitted with: Black rotary handle and drive shaft Number of poles Four-pole General

Accessories Actuator color Black Actuator type Short thumb-grip Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 10,000 Operations Mounting method Surface mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Main switch

Switch-disconnector

Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Intermediate mounting

Ground mounting

Distribution board installation Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 6 - 70 mm², flexible with ferrules to DIN 46228 Stripping length (main cable) 21 mm Tightening torque 7 Nm, Screw terminals Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) 10000 A Rated breaking capacity....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMM-160/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.