

INDUSTRIAL COMPONENT DATA

**DMV-3150/3N/M6/2HI11/K6-PG 6084847 Y8-6084847 EATON
ELECTRIC Switch disconnecter, 3 P + N + 2 N/O + 2 N/C, 3..**

Brand: EATON - MOELLER | Manufacturer Part Number: DMV-3150/3N/M6/2HI11/K6-PG



Manufacturer	EATON - MOELLER
MPN / Reference	DMV-3150/3N/M6/2HI11/K6-PG
Catalog number	Y8-6084847
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-04AE3B0E0C
Generated	2026-08-06

Product Overview

Switch disconnecter, 3 P + N + 2 N/O + 2 N/C, 3150 A, with handle gray and axle, mounting surface

DMV-3150/3N/M6/2HI11/K6-PG

Eaton DMV Switch-disconnector, 690 V, Three-pole + Neutral, Long turning handle, NEMA Other

Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMV, With gray rotary handle and drive shaft, Notes: visible contacts, Information about equipment supplied: including connection materials, 3 pole + N, Degree of Protection: IP00, IP20 with terminal cover, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 1400 kW, Rated uninterrupted current: I_u = 3150 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton DMV Switch-disconnector Catalog Number 6084847 Model Code DMV-3150/3N/M6/2HI11/K6-PG

EAN 8711426855038 Product Length/Depth 300 mm Product Height 377 mm Product Width 630 mm Product Weight 39 kg

Certifications IEC/EN 60947

VDE 0660

EAC

CE

RoHS

IEC/EN 60204

KEMA

IEC/EN 60947-3

Lloyds Features & Functions

Features Version as main switch Fitted with: Gray rotary handle and drive shaft Functions Interlockable Number of poles Three-pole + N General

Accessories Connection materials included with supplied equipment. Actuator color Gray Actuator type Long turning handle Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 5,000 Operations Mounting method Surface mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 12000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Ground mounting

Intermediate mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 3000 mm², Flat conductor connection with busbars Screw size M12 x 50 (2 x), Terminal screw Tightening torque 40 Nm, Screw terminals Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) 10000 A Rated breaking capac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMV-3150/3N/M6/2HI11/K6-PG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.