

INDUSTRIAL COMPONENT DATA

DMV-400/3/SE5/P-R 197341 Y7-197341 EATON ELECTRIC

DMV-400/3/SE5/P-R

Brand: EATON - MOELLER | Manufacturer Part Number: DMV-400/3/SE5/P-R



Manufacturer	EATON - MOELLER
MPN / Reference	DMV-400/3/SE5/P-R
Catalog number	Y7-197341
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-EBE2849D08
Generated	2026-08-06

Product Overview

DMV-400/3/SE5/P-R

Eaton DMV Switch-disconnector, DMV, 400 A, 3 pole, Emergency switching off function, With red rotary handle and yellow locking ring, in steel enclosure, 11 mm connection bore

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DMV Switch-disconnector Catalog Number 197341 Model Code DMV-400/3/SE5/P-R EAN

4015080894780 Product Length/Depth 225 mm Product Height 500 mm Product Width 400 mm Product Weight 12.5 kg

Certifications CE

IEC/EN 60947-3

IEC/EN 60947

VDE 0660

IEC/EN 60204 Features & Functions

Features Version as emergency stop installation

Version as main switch

Version as safety switch

Version as maintenance-/service switch Fitted with: Red rotary handle and yellow locking ring Functions Emergency switching off function

Interlockable Locking facility Lockable in the 0 (Off) position Number of poles Three-pole General
Accessories Auxiliary contact fitted by user. Connection type 11 mm connection bore Degree of protection NEMA 12
Degree of protection (front side) IP65 Lifespan, mechanical 10,000 Operations Mounting method Surface mounting
Mounting position As required Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand
voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for
Ground mounting Switching angle 90 ° Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min
-30 °C Ambient storage temperature - max 80 °C Terminal capacities
Terminal capacity 240 mm², Flat conductor connection with busbars Screw size M10 x 20, Terminal screw Tightening
torque 28 Nm, Screw termin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMV-400/3/SE5/P-R with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.