

INDUSTRIAL COMPONENT DATA

DMV-400/4/M4/P-G 6099274 Y8-6099274 EATON ELECTRIC
Switch-disconnector, 4 pole, 400 A, with grey knob, rear ..

Brand: EATON - MOELLER | Manufacturer Part Number: DMV-400/4/M4/P-G



Manufacturer	EATON - MOELLER
MPN / Reference	DMV-400/4/M4/P-G
Catalog number	Y8-6099274
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-3B71C2355E
Generated	2026-08-05

Product Overview

Switch-disconnector, 4 pole, 400 A, with grey knob, rear mounting, with 400 mm metal shaft

DMV-400/4/M4/P-G

Eaton DMV Switch-disconnector, DMV, 400 A, 4 pole, STOP function, with grey knob, With metal shaft for a control panel depth of 400 mm, 11 mm connection bore

Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMV, with grey knob, Notes: With metal shaft for a control panel depth of 400 mm, Information about equipment supplied: auxiliary contact fitted by user., 4 pole, Degree of Protection: Front IP65, Design: rear mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 180 kW, Rated uninterrupted current: Iu = 400 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DMV Switch-disconnector Catalog Number 6099274 Model Code DMV-400/4/M4/P-G EAN

8711426956124 Product Length/Depth 300 mm Product Height 150 mm Product Width 150 mm Product Weight 1.7 kg

Certifications IEC/EN 60204

IEC/EN 60947-3

KEMA

Lloyds

EAC

RoHS

VDE 0660

IEC/EN 60947

CE Catalog Notes Current for a time of 0.3 seconds Features & Functions

Features Version as main switch Fitted with: Metal shaft for a control panel depth of 400 mm

Gray knob Functions Interlockable

STOP function Locking facility Lockable in the 0 (Off) position Locking mechanism Padlocking feature SVC Number of poles Four-pole General

Accessories Auxiliary contact fitted by user. Actuator color Gray Actuator type Short thumb-grip Connection type 11 mm

connection bore Degree of protection NEMA 12 Degree of protection (front side) IP65 Lifespan, mechanical 10,000

Operations Mounting method Rear mounting Mounting position As required Overvoltage category III Pollution degree 3

Product Category Rated impulse withstand voltage (Uimp) 8000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Ground mounting

Intermediate mounting Switching angle 90 ° Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 240 mm², Flat conductor connection with busbars S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMV-400/4/M4/P-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.