

INDUSTRIAL COMPONENT DATA

MSC-D-10-M9(24V50HZ) 115946 Y7-115946 EATON ELECTRIC DOL starter, 3p, 4.0kW / 400V / AC3, 100kA

Brand: EATON - MOELLER | Manufacturer Part Number: MSC-D-10-M9(24V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	MSC-D-10-M9(24V50HZ)
Catalog number	Y7-115946
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-9AF4EAD2B0
Generated	2026-08-05

Product Overview

DOL starter, 3p, 4.0kW / 400V / AC3, 100kA

MSC-D-10-M9(24V50HZ)

Eaton Moeller® series MSC-D DOL starter, 380 V 400 V 415 V: 4 kW, I_r= 6.3 - 10 A, 24 V 50 Hz, AC

Pre-mounted motor starter with minimized wiring time consisting of motor-protective circuit-breaker and contactor

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

Additional Product Information

General specifications

Product Name Eaton Moeller® series MSC-D DOL starter Catalog Number 115946 Model Code MSC-D-10-M9(24V50HZ)

EAN 4015081156863 Product Length/Depth 95 mm Product Height 180 mm Product Width 45 mm Product Weight 0.58 kg

Certifications IEC/EN 60947-4-1

VDE 0660

CSA Class No.: 3211-24

CSA File No.: 012528

UL Category Control No.: NKJH

UL60947-4-1A

CSA-C22.2 No. 14-10

UL

UL File No.: E123500

CE

CSA Features & Functions

Fitted with: Short-circuit release Functions Temperature compensated overload protection General

Class CLASS 10 A Connection Screw terminals Connection to SmartWire-DT No Coordination type 1 Degree of protection IP20

NEMA Other Model IEC/UL starter Mounting method DIN rail Number of auxiliary contacts (normally closed contacts) 0

Number of auxiliary contacts (normally open contacts) 1 Overload release current setting - min 6.3 A Overload release current setting - max 10 A Overvoltage category III Pollution degree 3 Rated impulse withstand voltage (Uimp) 6000 V AC Suitable for Also motors with efficiency class IE3 Type Starter with Bi-Metal release Voltage type AC Climatic environmental conditions

Altitude Max. 2000 m Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Electrical rating

Rated operational current (Ie) 8.5 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V 9 A Rated operational power at AC-3, 220/230 V, 50 Hz 2.2 kW Rated operational power at AC-3, 380/400 V, 50 Hz 4 kW Rated operationa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend EATON - MOELLER / MSC-D-10-M9(24V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.