

INDUSTRIAL COMPONENT DATA

MSC-DE-32-M17(230V50HZ) 121747 Y7-121747 EATON ELECTRIC DOL starter, 3p, 7.5kW/400V/AC3, 100kA, protection e..

Brand: EATON - MOELLER | Manufacturer Part Number: MSC-DE-32-M17(230V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	MSC-DE-32-M17(230V50HZ)
Catalog number	Y7-121747
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-1D0DD115A6
Generated	2026-08-06

Product Overview

DOL starter, 3p, 7.5kW/400V/AC3, 100kA, protection electronic

MSC-DE-32-M17(230V50HZ)

DOL starter, 380 V 400 V 415 V: 7.5 kW, Iq= 100 kA, Ir= 8 - 32 A, 230 V 50 Hz, 240 V 60 Hz, AC voltage

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

DOL starter, 380 V 400 V 415 V: 7.5 kW, Iq= 100 kA, Ir= 8 - 32 A, 230 V 50 Hz, 240 V 60 Hz, AC voltage DOL starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor ratings Motor rating AC-3 380 V 400 V 415 V: P= 7.5 kW, Motor ratings Motor rating AC-3 500 V: P= 7.5 kW, Motor ratings Rated operational current AC-3 500 V: Ie= 12.1 A, Motor ratings Rated conditional short-circuit current 500 V: Iq= 50 kA, Setting range of overload releases: Ir= 8 - 32 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, AC voltage, Standards: IEC/EN 60947-4-1, VDE 0660 Delivery program

Basic function DOL starters (complete devices) Basic device MSC Notes Also suitable for motors with efficiency class IE3. IE3-ready devices are identified by the logo on their packaging. Connection to SmartWire-DT no Motor ratings Motor rating [P]AC-3380 V 400 V 415 V [P] 7.5 kW Motor rating [P]AC-3500 V [P] 7.5 kW Rated operational currentAC-3380 V 400 V 415 V [Ie] 12.1 A Rated operational currentAC-3500 V [Ie] 12.1 A Rated short-circuit current 380 - 415 V [Iq] 100 kA Rated

conditional short-circuit current 500 V [Iq] 50 kA Setting range Setting range of overload releases[Ir] 8 - 32 A Coordination
Type of coordination "1"

Type of coordination "2" Contact sequence Actuating voltage 230 V 50 Hz, 240 V 60 Hz AC voltage Motor-protective
circuit-breakers....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MSC-DE-32-M17(230V50HZ) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.