

INDUSTRIAL COMPONENT DATA

PKE-XH 142416 Y7-142416 EATON ELECTRIC Door coupling handle, black, for PKE

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-XH



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-XH
Catalog number	Y7-142416
Category	Door coupling handle for switchgear
Minimum order	1 Pcs
Document ID	EO-5B7A3B7C22
Generated	2026-08-02

Product Overview

Door coupling handle, black, for PKE

PKE-XH

Eaton Moeller® series PKE Door coupling handle, black, for PKE

Door coupling rotary handle for use as main switch according to EN 60204 having plug-in extension shaft PKZ0-XAH, can be cut to desired length for mounting depths from 100...200 mm. Carrier with extension shaft included as standard. With ON/OFF switch position and "+" (tripped), lockable in the off position with 3 padlocks 4...8 hasp thickness

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Electronic Circuit Breakers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Door coupling handle Catalog Number 142416 Model Code PKE-XH EAN 4015081391424 Product Length/Depth 235 mm Product Height 66 mm Product Width 64 mm Product Weight 0.16 kg Certifications CSA

UL

UL 508

UL Category Control No.: NLRV

CSA Class No.: 3211-05

CE

UL File No.: E36332

CSA File No.: 165628

CSA-C22.2 No. 14

IEC/EN 60947-4-1 Catalog Notes Cannot be used in combination with VHI20-PKZ0. Features & Functions

Color Black Features Lockable Fitted with: Axis extension

ON/OFF switch position and "+" (tripped), lockable

3 padlocks, 4 - 8 mm hasp thickness

Door interlock General

Degree of protection IP65

NEMA 4X, 12 Product Category Accessories Suitable as Main switch to IEC/EN 60204 Used with PKE-XH Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abn...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-XH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.