

INDUSTRIAL COMPONENT DATA

PKZ0-XRH-MCC 106137 Y7-106137 EATON ELECTRIC Door coupling handle, for MCC, 90 degree, NA type

Brand: EATON - MOELLER | Manufacturer Part Number: PKZ0-XRH-MCC



Manufacturer	EATON - MOELLER
MPN / Reference	PKZ0-XRH-MCC
Catalog number	Y7-106137
Category	Handle for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-F3DE3E9502
Generated	2026-08-05

Product Overview

Door coupling handle, for MCC, 90 degree, NA type

PKZ0-XRH-MCC

Eaton Moeller® series PKZ0 Door coupling handle, for MCC, 90 degree, NA type PKZ0-XRH-MCC

Door coupling handle, Product range: Accessories, For use as a main switch with Emergency-Stop function to EN 60204 in MCC power distribution systems and with PKZM0 installed when rotated by 90°, Red-yellow, For use with: PKZM0, PKZM4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZ0 Accessory Door coupling handle Catalog Number 106137 Model Code PKZ0-XRH-MCC EAN 4015081059072 Product Length/Depth 235 mm Product Height 66 mm Product Width 64 mm Product Weight 0.16 kg Certifications UL File No.: E36332

UL 508

CSA

UL

CE

CSA File No.: 165628

IEC/EN 60947-4-1

UL Category Control No.: NLRV

CSA Class No.: 3211-05

CSA-C22.2 No. 14 Catalog Notes Cannot be used in combination with VHI20-PKZ0. Features & Functions

Color Red Features Lockable Fitted with: 3 padlocks, 4 - 8 mm hasp thickness

Extension shaft

ON/OFF switch position and "+" (tripped), lockable General

Product Category Accessories Suitable as Main switch with Emergency-Stop function to EN 60204 in MCC power distribution systems and with PKZM0 installed when rotated by 90° Suitable for Emergency stop Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Mee...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZ0-XRH-MCC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.