

INDUSTRIAL COMPONENT DATA

PKZ0-XH-MCC 106136 Y7-106136 EATON ELECTRIC Door coupling handle, for MCC-V, 90 degree, twisted

Brand: EATON - MOELLER | Manufacturer Part Number: PKZ0-XH-MCC



Manufacturer	EATON - MOELLER
MPN / Reference	PKZ0-XH-MCC
Catalog number	Y7-106136
Category	Handle for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-CDFB4ACC91
Generated	2026-08-05

Product Overview

Door coupling handle, for MCC-V, 90 degree, twisted

PKZ0-XH-MCC

Eaton Moeller® series PKZ0 Door coupling handle, for MCC-V, 90 degree, twisted

Door coupling handle, Product range: Accessories, For use as a main switch to EN 60204 in MCC power distribution systems and with PKZM0 installed when rotated by 90°, Black, For use with: PKZM0, PKZM4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZ0 Accessory Door coupling handle Catalog Number 106136 Model Code PKZ0-XH-MCC EAN 4015081059065 Product Length/Depth 235 mm Product Height 66 mm Product Width 64 mm Product Weight 0.16 kg Compliances CE Marked Certifications UL 508

CSA Std. C22.2 No. 14

IEC 60947-4-1

CSA Certified

UL Listed

CSA Class No.: 3211-05

IEC/EN 60947-4-1

UL Category Control No.: NLRV

CSA-C22.2 No. 14

UL

CSA

UL File No.: E36332

CE

CSA File No.: 165628 Catalog Notes Cannot be used in combination with VHI20-PKZ0. Features & Functions

Color Black Features Lockable Fitted with: Extension shaft

ON/OFF switch position and "+" (tripped), lockable

3 padlocks, 4 - 8 mm hasp thickness General

Product Category Accessories Suitable as Main switch to EN 60204 in MCC power distribution systems and with PKZM0 installed when rotated by 90° Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification

Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdis 0 W Heat dissipation per pole,

current-dependent Pvid 0 W Rated operational current for specified heat dissipation (In) 0 A Static heat dissipation,

non-current-dependent Pvs 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZ0-XH-MCC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.