

INDUSTRIAL COMPONENT DATA

PKE-XRH-MCC 142419 Y7-142419 EATON ELECTRIC Door coupling handle, red yellow, MCC, 90 degree, for PKE

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-XRH-MCC



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-XRH-MCC
Catalog number	Y7-142419
Category	Door coupling handle for switchgear
Minimum order	1 Pcs
Document ID	EO-F2C861F1A8
Generated	2026-08-05

Product Overview

Door coupling handle, red yellow, MCC, 90 degree, for PKE

PKE-XRH-MCC

Eaton Moeller® series PKE Door coupling handle, red yellow, MCC, 90 degree, for PKE

Door coupling rotary handle for use as main switch with EMERGENCY SWITCHING OFF function according to EN 60204 in MCC distribution board having built-in PKE rotated by 90 degrees plug-in extension shaft PKZ0-XAH, can be cut to desired length for mounting depths from 100...200 mm. Carrier with extension shaft included as standard. With ON/OFF switch position and "+" (tripped), lockable in the off position with 3 padlocks 4...8 hasp thickness

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Electronic Circuit Breakers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Door coupling handle Catalog Number 142419 Model Code PKE-XRH-MCC

EAN 4015081391455 Product Length/Depth 235 mm Product Height 66 mm Product Width 64 mm Product Weight 0.16 kg

Certifications CSA File No.: 165628

IEC/EN 60947-4-1

UL Category Control No.: NLRV

CSA

CSA Class No.: 3211-05

CE

UL
UL 508
CSA-C22.2 No. 14
UL File No.: E36332 Catalog Notes Cannot be used in combination with VHI20-PKZ0. Features & Functions
Color Red
Yellow Features Lockable Fitted with: Axis extension
Door interlock
3 padlocks, 4 - 8 mm hasp thickness
Handle red/yellow
ON/OFF switch position and "+" (tripped), lockable General
Degree of protection IP65
NEMA 4X, 12 Product Category Accessories Suitable as Main switch with Emergency-Stop function to EN 60204 in MCC power distribution systems and with PKE installed when rotated by 90° Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification
Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-XRH-MCC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.