

INDUSTRIAL COMPONENT DATA

XVTL-DG-10-16-L 114661 EATON ELECTRIC Door, glass, left, for HxW 1600x1000mm

Brand: EATON - MOELLER | Manufacturer Part Number: XVTL-DG-10-16-L



Manufacturer	EATON - MOELLER
MPN / Reference	XVTL-DG-10-16-L
Catalog number	114661
Category	Door/operating panel (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-224097CAA0
Generated	2026-08-06

Product Overview

Door, glass, left, for HxW=1600x1000mm
door, clear, left, for HxA=1600x1000mm
Glass door with hinges and locking swinghandle

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

Switch disconnecter, low voltage, 1600 A, AC 400 V, NH4a, AC22B, 3P, IEC, plate mounting, 3-phase simultaneous switching Fuse accessory, Switch disconnecter, low voltage, 1600 A, AC 400 V, NH4a, AC22B, 3P, IEC, Horizontal, mounting plate type, 3-phase simultaneous switching, M12 screws, NH4a fuse-links, IEC 60947-1, IEC 60947-3, IP20 [Delivery program

Product range Fuse accessory Basic function Switch disconnecter Field of application low voltage Rated current [I] 1600 A Rated voltage AC 400 V Construction size NH4a Utilization category AC22B Description mounting plate type 3-phase simultaneous switching

M12 screws Protection IP20 Number of poles 3P usable for size/applications NH4a fuse-links Standard/Approval IEC Shape Horizontal Standards/Regulations IEC 60947-1

IEC 60947-3 , Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040) Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter () [AKF058013]) Version as main switch No Version as safety switch No Max. rated operation

voltage Ue AC 690 V Rated permanent current Iu 1600 A Rated operation power at AC-23, 400 V 640 kW Conditioned
rated short-circuit current Iq 50 kA Rated short-time withstand current Icw 50 kA Suitable for fuses NH4a Number of poles 3
With error protection No Type of electrical connection of main circuit Screw connection...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVTL-DG-10-16-L with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.